

Features

- Low on-resistance
- JESD22-A114-B ESD rating of class 2 per human body model
- High-speed switching
- Drive circuits can be simple
- Parallel use is easy


HF

Typical Applications

- N-channel enhancement mode effect transistor
- Switching application


Mechanical Data

- Case: SOT-23, SOT-323, SOT-523, DFN1006-3, SOT-723
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208




2N5003

SOT-23




2N5003W

SOT-323




2N5003T

SOT-523




2N5003L

DFN1006-3



2N5003M

SOT-723



Ordering Information

Part Number	Package	Shipping	Marking Code
2N5003	SOT-23	3000pcs / Tape & Reel	5003
2N5003W	SOT-323	3000pcs / Tape & Reel	5003
2N5003T	SOT-523	3000pcs / Tape & Reel	53
2N5003L	DFN1006-3	10000pcs / Tape & Reel	53
2N5003M	SOT-723	10000pcs / Tape & Reel	5003

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter		Symbol	Value	Units
Drain-Source Voltage		V_{DS}	50	V
Gate -Source Voltage		V_{GS}	± 20	V
Continuous Drain Current ^{*1}		I_D	300	mA
Pulsed Drain Current ($t_p = 10\mu\text{s}$) ^{*1}		I_{DM}	2000	mA
Power Dissipation ^{*1}	SOT-23	P_D	0.35	W
	SOT-323		0.25	
	SOT-523		0.15	
	DFN1006-3		0.15	
	SOT-723		0.15	

Thermal Characteristics

Parameter		Symbol	Limits	Unit
Thermal Resistance Junction to Ambient Air ^{*1}	SOT-23	$R_{\theta JA}$	357	$^\circ\text{C/W}$
	SOT-323		500	
	SOT-523		833	
	DFN1006-3		833	
	SOT-723		833	
Thermal Resistance Junction to Lead ^{*1}	SOT-23	$R_{\theta JL}$	234	$^\circ\text{C/W}$
	SOT-323		313	
	SOT-523		521	
	DFN1006-3		521	
	SOT-723		521	
Thermal Resistance Junction to Case ^{*1}	SOT-23	$R_{\theta JC}$	195	$^\circ\text{C/W}$
	SOT-323		261	
	SOT-523		434	
	DFN1006-3		434	
	SOT-723		434	
Operating Junction Temperature Range		T_J	-55 to +150	$^\circ\text{C}$
Storage Temperature Range		T_{STG}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test conditions	MIN	TYP	MAX	UNIT
OFF Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	50	-	-	V
Δ V _{(BR)DSS} /ΔT _J	Breakdown Voltage Temp. Coefficient	I _D = 250μA	-	66	-	mV/°C
I _{DSS}	Drain to Source Leakage Current	V _{DS} = 50V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-body Leakage	V _{GS} = ±20V, V _{DS} = 0V	-	-	±10	μA
ON Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *2	V _{GS} = 10V, I _D = 0.5A	-	1.2	1.5	Ω
		V _{GS} = 4.5V, I _D = 0.2A	-	1.5	2.5	
		V _{GS} = 2.5V, I _D = 0.2A	-	1.6	2.9	
		V _{GS} = 1.8V, I _D = 0.05A	-	2.8	3.2	
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250uA	0.5	0.8	1.0	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	34	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = 20V f = 1.0MHz	-	41	-	pF
C _{OSS}	Output Capacitance		-	15	-	
C _{RSS}	Reverse Transfer Capacitance		-	4	-	
g _{fs}	Forward Transconductance	V _{DS} = 10V, I _D = 0.2A	-	0.5	-	S
Switching Characteristics						
t _{d(on)}	Turn-on Delay Time *3	V _{DD} = 30V, I _D = 0.2A V _{GS} = 10V, R _G = 25Ω R _L = 150Ω	-	6	-	nS
t _r	Turn-on Rise Time *3		-	5	-	
t _{d(off)}	Turn-Off Delay Time *3		-	25	-	
t _f	Turn-Off Fall Time *3		-	15	-	
Q _G	Total Gate-Charge	V _{DD} = 25V	-	4	-	nC
Q _{GS}	Gate to Source Charge	V _{GS} = 10V	-	0.6	-	
Q _{GD}	Gate to Drain (Miller) Charge	I _D = 0.2A	-	0.46	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *2	I _S = 0.3A, V _{GS} = 0V	-	0.85	1.2	V
I _S	Diode Continuous Forward Current	T _C = 25°C	-	-	0.3	A

Notes:

- The data tested by surface mounted on a FR-4 board
- The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
- Guaranteed by design, not subject to production

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Typical Output Characteristics




Fig 2 On-Resistance vs. Drain Current
and Gate Voltage




Fig 3 On-Resistance vs. Gate-Source Voltage




Fig 4 Body-Diode Characteristics




Fig 5 Normalized On-Resistance vs. Junction
Temperature




Fig 6 Transfer Characteristics




Fig 7 Capacitance Characteristics




Fig 8 Gate-Charge Characteristics




Fig 9 Normalized Breakdown Voltage
vs. Junction Temperature




Fig 10 Normalized $V_{GS(th)}$ vs. Junction Temperature




Fig 11 Safe Operation Area






Fig 12 Normalized Maximum transient thermal
impedance


Package Outline Dimensions (Unit: mm)




SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60




SOT-323		
Dimension	Min.	Max.
A	2.00	2.20
B	1.15	1.35
C	0.90	1.10
D	0.15	0.35
E	0.25	0.40
G	1.20	1.40
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40



SOT-523		
Dimension	Min.	Max.
A	1.50	1.70
B	0.75	0.85
C	0.60	0.80
D	0.15	0.30
E	0.30	0.40
F	0.25	0.40
G	0.90	1.10
H	0.02	0.10
J	0.08	0.18
K	1.45	1.75




DFN1006-3			
Dimension	Min.	Typ.	Max.
A	0.95	1.00	1.075
B	0.47	0.50	0.53
C	0.55	0.60	0.675
D	0.45	0.50	0.55
E/J	0.20	0.25	0.30
F	-	0.40	-
G	-	0.35	-
H	0	0.03	0.05
I	0.10	0.15	0.20




SOT-723		
Dim	Min	Max
A	1.10	1.30
B	0.70	0.90
C	0.40	0.54
D	0.22	0.42
E	0.10	0.30
F	0.12	0.32
G	0.70	0.90
J	0.08	0.15
K	1.10	1.30

Mounting Pad Layout (Unit: mm)


SOT-23




SOT-323




SOT-523



DFN1006-3



SOT-723



IMPORTANT NOTICE

Galaxy Microelectronics (GME) reserves the right to make changes without further notice to any product herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.