


Features

- ESD / transient protection of high speed data lines
 - IEC 61000-4-2 (ESD): ± 30 kV (air), ± 30 kV (contact)
- Working voltage: $V_{RWM} = 15V$
- Low reverse clamping voltage
- RoHS compliant with Halogen-free

HF



SOD-323

Mechanical Data

- Case: SOD-323
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
GESD15VS1B3	SOD-323	3000 pcs / Tape & Reel	B15

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
IEC 61000-4-2; ESD (Air)	V_{ESD-A}	± 30	kV
IEC 61000-4-2; ESD (Contact)	V_{ESD-C}	± 30	kV
Peak Pulse Power ($t_p = 8/20\mu\text{s}$)	P_{PP}	180	W
Peak Pulse Current ($t_p = 8/20\mu\text{s}$)	I_{PP}	6	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	200	mW
Junction Temperature	T_J	$-55 \sim +125$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ\text{C}$

Electrical Characteristics (@ $T_A = 25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Stand-off Voltage	V_{RWM}		-	-	15	V
Reverse Breakdown Voltage	$V_{(BR)}$	$I_T = 1\text{mA}$	16.2	-	20.5	V
Reverse Leakage Current	I_R	$V_{RWM} = 15\text{V}$	-	-	0.1	μA
Clamping Voltage	V_C	$I_{PP} = 1\text{A}$, $t_p = 8/20\mu\text{s}$	-	20	22	V
		$I_{PP} = 6\text{A}$, $t_p = 8/20\mu\text{s}$	-	-	30	V
Junction Capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$	-	-	25	pF

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 8/20 μs waveform per IEC61000-4-5




Fig 2 ESD pulse waveform according to IEC61000-4-2




Fig 3 Power Derating Curve




Fig 4 Clamping Voltage vs. Peak Pulse Current





Fig 5 Capacitance vs. Reverse Voltage

Package Outline Dimensions (Unit: mm)



SOD-323		
Dimension	Min.	Max.
A	1.60	1.80
B	1.20	1.40
C	0.80	0.90
D	0.25	0.35
E	0.22	0.42
H	0.02	0.10
J	0.05	0.15
K	2.55	2.75

Package Outline Dimensions (Unit: mm)

SOD-323

