


Features

- Low leakage current
- Working voltage: $V_{RWM} = 24V$
- Halogen free
- Qualified to AEC-Q101 standards for high reliability
- ESD / transient protection of high speed data lines
 - IEC 61000-4-2 (ESD): ± 23 kV (air), ± 23 kV (contact)

HF



SOD-323

Mechanical Data

- Case: SOD-323
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TGESD24VB3	SOD-323	3000 pcs / Tape & Reel	N24

Maximum Ratings (@ $T_A = 25^\circ C$ unless otherwise specified)

Parameter	Symbol	Value	Unit
IEC 61000-4-2; ESD (Air)	V_{ESD-A}	± 23	kV
IEC 61000-4-2; ESD (Contact)	V_{ESD-C}	± 23	kV
Reverse Stand-off Voltage	V_{RWM}	24	V
Peak Pulse Power ($t_p = 8/20\mu s$)	P_{PP}	160	W
Peak Pulse Current ($t_p = 8/20\mu s$)	I_{PP}	3	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Operating Temperature	T_J	$-55 \sim +125$	$^\circ C$
Storage Temperature	T_{STG}	$-55 \sim +150$	$^\circ C$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$	26.5	-	-	V
Reverse Leakage Current	I_R	$V_{RWM} = 24\text{V}$	-	-	50	nA
Clamping Voltage	V_C	$I_{PP} = 1\text{A}$, ($t_p = 8/20\mu\text{s}$)	-	-	36	V
		$I_{PP} = 3\text{A}$, ($t_p = 8/20\mu\text{s}$)	-	-	70	V
Diode Capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$	-	-	25	pF

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig. 1 8/20 μs waveform per IEC61000-4-5




Fig. 2 ESD pulse waveform according to IEC61000-4-2




Fig. 3 Power Derating Curve





Fig. 4 Clamping Voltage vs. Peak Pulse Current


Package Outline Dimensions (Unit: mm)



SOD-323		
Dimension	Min.	Max.
A	1.60	1.80
B	1.20	1.40
C	0.80	0.90
D	0.25	0.35
E	0.22	0.42
H	0.02	0.10
J	0.05	0.15
K	2.55	2.75

Package Outline Dimensions (Unit: mm)

SOD-323



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.