


NPN SILICON EPITAXIAL TRANSISTOR POWER MINI MOLD

2SC3357

FEATURES

- Low Noise and High Gain
NF = 1.1 dB TYP., Ga = 8.0 dB TYP. @VCE = 10 V,
IC = 7 mA, f = 1.0 GHz
NF = 1.8 dB TYP., Ga = 9.0 dB TYP. @VCE = 10 V,
- Large PT in Small Package
PT : 2 W with 16 cm²* 0.7 mm Ceramic Substrate.
- RoHS compliant with Halogen-free

HF



APPLICATIONS

- The 2SC3357 is an NPN silicon epitaxial transistor designed For low noise amplifier at VHF, UHF and CATV band.
- It has large dynamic range and good current characteristic.

ORDERING INFORMATION

Type No.	Marking	Package Code
2SC3357-H	RH	SOT-89
2SC3357-F	RF	SOT-89
2SC3357-E	RE	SOT-89

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Symbol	Parameter	Value	Units
V _{CBO}	Collector-Base Voltage	20	V
V _{CEO}	Collector-Emitter Voltage	12	V
V _{EBO}	Emitter-Base Voltage	3.0	V
I _C	Collector Current -Continuous	100	mA
P _T 备注 1	Total Power Dissipation	1.2	W
R _{th(j-a)} 备注 1	Thermal Resistance	62.5	°C/W
T _j	Junction Temperature	150	°C
T _{stg}	Storage Temperature	-65 to +150	°C

备注 1: mounted on 16 cm² × 0.7 mm Ceramic Substrate

NPN SILICON EPITAXIAL TRANSISTOR POWER MINI MOLD

2SC3357

ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C=10\mu A$	20			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=1mA$	12			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=10\mu A$	3.0			V
Collector cut-off current	I_{CBO}	$V_{CB}=10V, I_E=0$			1	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=1.0V, I_C=0$			1	μA
DC current gain	h_{FE} 备注 2	$V_{CE}=10V, I_C=20mA$	50	120	300	
Transition frequency	f_T	$V_{CE}=10V, I_C=20mA$		6.5		GHz
Feed-Back Capacitance	C_{re} 备注 3	$V_{CB} = 10 V, I_C = 0 mA, f = 1.0 MHz$		0.65	1.0	pF
Insertion power gain	$ S_{21e} ^2$	$V_{CE}=10V, I_C=20mA, f=1GHz$		9		dB
Noise Figure	NF	$V_{CE}=10V, I_C=7mA, f=1GHz$		1.1		dB
Noise Figure	NF	$V_{CE}=10V, I_C=40mA, f=1GHz$		1.8	3.0	dB

备注 2: Pulse Measurement $PW \leq 350 \mu s$, Duty Cycle $\leq 2 \%$

备注 3: The emitter terminal and the case shall be connected to the guard terminal of the three-terminal capacitance bridge.

CLASSIFICATION OF h_{FE}

Rank	H	F	E
Range	50-100	80-160	125-250
MARKING	RH	RF	RE

NPN SILICON EPITAXIAL TRANSISTOR POWER MINI MOLD

2SC3357

TYPICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified

Fig.1 TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE




Fig.2 FEED-BACK CAPACITANCE vs. COLLECTOR TO BASE VOLTAGE




Fig.3 DC CURRENT GAIN vs. COLLECTOR CURRENT





Fig.4 INSERTION GAIN vs. COLLECTOR CURRENT



NPN SILICON EPITAXIAL TRANSISTOR POWER MINI MOLD

2SC3357

Fig.5 GAIN BANDWIDTH PROUDCT vs. COLLECTOR CURRENT




Fig.6 INSERTION GAIN, MAXIMUM GAIN vs. FREQUENCY




Fig.7 NOISE FIGURE vs. COLLECTOR CURRENT





Fig.8 INTERMODULATION DISTORTION vs. COLLECTOR CURRENT




NPN SILICON EPITAXIAL TRANSISTOR POWER MINI MOLD

2SC3357


PACKAGE OUTLINE

Plastic surface mounted package

SOT-89



SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
2SC3357	SOT-89	1000 pcs / Tape & Reel