Zener Diode
AZ23B33


Features

- Tight voltage tolerance: ±2%
- Ultra low-profile package well suited for automated assembly
- Moisture sensitivity level 1
- RoHS compliant with Halogen-free

HF

Mechanical Data

- Case: SOT-23
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



SOT-23

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
AZ23B33	SOT-23	3000 pcs / Tape & Reel	D67

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	300	mW
Thermal Resistance Junction-to-Air *1	$R_{\theta JA}$	340	°C/W
Thermal Resistance Junction-to-Case *1	$R_{\theta JC}$	260	°C/W
Thermal Resistance Junction-to-Lead *1	$R_{\theta JL}$	270	°C/W
Operating Junction Temperature Range	T_J	-55 ~ +150	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 1 inch^2 FR-4 board with 2OZ copper

Electrical Characteristics (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Zener Voltage	V_Z	I_{ZT} = 5mA	32.34	33.0	33.66	V
Forward Voltage	V_F	I_F = 10mA	-	-	0.9	V
Maximum Reverse Current	I_R	V_R = 25V	-	-	0.1	μA
Maximum Zener Impedance	Z_{ZT}	I_{ZT} = 5mA	-	-	80	Ω
Maximum Zener Impedance	Z_{ZK}	I_{ZK} = 1mA	-	-	250	Ω
Temperature Coefficient	T_C	I_{ZT} = 5mA	-	29.8	-	mV/°C

TYPICAL CHARACTERISTICS (@ T_A = 25°C unless otherwise specified)




Fig 1 Steady State Power Derating




Fig 2 Typical Zener Breakdown Characteristics




Fig 3 Zener Impedance vs. Zener Current




Fig 4 Typical Forward Characteristics





Fig 5 Typical Reverse Characteristics

Package Outline Dimensions (Unit: mm)



SOT-23		
Dimension	**Min.**	**Max.**
A	2.70	3.10
B	1.10	1.50
C	0.9	1.1
D	0.3	0.5
E	0.35	0.48
G	1.80	2.00
H	0.02	0.1
J	0.05	0.15
K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23

