
High Speed Switching Diode

BAS516

Features


HF

- High switching speed
- Continuous reverse voltage
- Repetitive peak reverse voltage
- Repetitive peak forward current



Typical Applications

- High-speed switching in surface mounted circuits



SOD-523

Mechanical Data

- Case: SOD-523
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BAS516	SOD-523	3000 pcs / Tape & Reel	61

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Repetitive Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_R	100	V
Continuous Forward Current	I_F	250	mA
Repetitive Forward Current	I_{FRM}	500	mA
Peak Forward Surge Current, t_p = 1μs	I_{FSM}	4	A
Peak Forward Surge Current, t_p = 1ms	I_{FSM}	1	A
Peak Forward Surge Current, t_p = 1s	I_{FSM}	0.5	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	200	mW
Thermal Resistance Junction-to-Air *1	$R_{\theta JA}$	458	°C/W
Thermal Resistance Junction-to-Case *1	$R_{\theta JC}$	286	°C/W
Thermal Resistance Junction-to-Lead *1	$R_{\theta JL}$	324	°C/W
Operating Junction Temperature Range	T_J	-65 ~ +150	°C
Storage Temperature Range	T_{STG}	-65 ~ +150	°C

Electrical Characteristics (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	I_F = 1.0mA	-	-	0.715	V
		I_F = 10mA	-	-	0.855	
		I_F = 50mA	-	-	1.0	
		I_F = 150mA	-	-	1.25	
Maximum Peak Reverse Current	I_R	V_R = 25V, T_J = 25°C	-	-	30	nA
		V_R = 25V, T_J = 125°C	-	-	30	μA
		V_R = 75V, T_J = 25°C	-	-	1	
		V_R = 75V, T_J = 150°C	-	-	50	
Total Capacitance	C_J	V_R = 0V, f = 1.0MHz	-	-	1	pF
Reverse Recovery Time	t_{rr}	I_F = I_R = 10mA, R_L = 400Ω	-	-	4	ns

Note 1: The data tested by surface mounted on a 15mm * 15mm * 1mm FR4-epoxy P.C.B

Ratings and Characteristic Curves (@ T_A = 25°C unless otherwise specified)




Fig 1 Typical Reverse Characteristic




Fig 2 Typical Forward Characteristic




Fig 3 Current Derating Curve




Fig 4 Current Derating Curve




Fig 5 Non-repetitive peak forward current as a function of pulse duration; maximum values





Fig 6 Diode capacitance as a function of reverse voltage; typical values


Package Outline Dimensions (Unit: mm)



SOD-523		
Dimension	**Min.**	**Max.**
A	1.10	1.30
B	0.70	0.90
C	0.50	0.70
D	0.25	0.35
E	0.15	0.25
J	0.05	0.15
K	1.50	1.70

Mounting Pad Layout (Unit: mm)

SOD-523



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.