



Features

- Extremely fast switching speed
- Low forward voltage

HF

Mechanical Data

- Case: SOD-323
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOD-323

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BAT54H	SOD-323	3000 pcs / Tape & Reel	JV

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
DC Reverse Voltage	V _R	30	V
Maximum Average Forward Output Current	I _{F(AV)}	0.2	A
Peak Forward Surge Current (1s single half sine-wave)	I _{FSM}	0.6	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	200	mW
Thermal Resistance Junction-to-Air ^{*1}	R _{θJA}	424	°C/W
Thermal Resistance Junction-to-Case ^{*1}	R _{θJC}	234	°C/W
Thermal Resistance Junction-to-Lead ^{*1}	R _{θJL}	312	°C/W
Operating Junction Temperature	T _J	-55 ~ +125	°C
Storage Temperature Range	T _{STG}	-65 ~ +125	°C

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 100\mu\text{A}$	30	-	-	V
Forward Voltage *2	V_F	$I_F = 0.1\text{mA}$	-	-	240	mV
		$I_F = 1\text{mA}$	-	-	320	mV
		$I_F = 10\text{mA}$	-	-	400	mV
		$I_F = 30\text{mA}$	-	-	500	mV
		$I_F = 100\text{mA}$	-	-	800	mV
Maximum Peak Reverse Current *3	I_R	$V_R = 25\text{V}$	-	-	50	μA
Reverse Recovery Time	t_{rr}	$I_F = I_R = 10\text{mA}$ $I_{rr} = 0.1I_R$, $R_L = 100\Omega$	-	-	5	ns
Capacitance Between Terminals	C_T	$V_R = 1\text{V}$, $f = 1\text{MHz}$	-	-	10	pF

Notes:

1. The data tested by surface mounted on a 15mm * 15mm * 1mm FR4-epoxy P.C.B
2. Pulse test, $t_p \leq 300\mu\text{s}$
3. Pulse test, $t_p \leq 5\text{ms}$

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Typical Reverse Characteristic




Fig 2 Typical Forward Characteristics




Fig 3 Capacitance Characteristics





Fig 4 Derating Curve


Package Outline Dimensions (Unit: mm)



SOD-323		
Dimension	Min.	Max.
A	1.60	1.80
B	1.20	1.40
C	0.80	0.90
D	0.25	0.35
E	0.22	0.42
H	0.02	0.10
J	0.05	0.15
K	2.55	2.75

Mounting Pad Layout (Unit: mm)

SOD-323



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.