

Features


- Fast switching speed
- High reverse breakdown voltage
- Low leakage current

HF

Mechanical Data

- Case: SOD-323
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

1 CATHODE 2 ANODE



SOD-323

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BAV5004WS	SOD-323	3000 pcs / Tape & Reel	LY

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Repetitive Peak Reverse Voltage	V _{RRM}	400	V
Working Peak Reverse Voltage	V _{RWM}	350	V
DC Blocking Voltage	V _R	350	V
RMS Reverse Voltage	V _{R(RMS)}	247	V
Forward Continuous Current	I _F	225	mA
Repetitive Peak Forward Current	I _{FRM}	625	mA
Non-Repetitive Peak Forward Surge Current, t _p = 1μs	I _{FSM}	5	A
Non-Repetitive Peak Forward Surge Current, t _p = 1ms	I _{FSM}	3	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	200	mW
Thermal Resistance Junction-to-Air *1	R _{θJA}	300	°C/W
Thermal Resistance Junction-to-Case *1	R _{θJC}	180	°C/W
Thermal Resistance Junction-to-Lead *1	R _{θJL}	240	°C/W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 150\mu\text{A}$	400	-	-	V
Forward Voltage	V_F	$I_F = 20\text{mA}$	-	-	0.93	V
		$I_F = 100\text{mA}$	-	-	1.09	V
		$I_F = 200\text{mA}$	-	-	1.29	V
Maximum Peak Reverse Current	I_R	$V_R = 240\text{V}, T_J = 25^\circ\text{C}$	-	-	1	μA
		$V_R = 240\text{V}, T_J = 150^\circ\text{C}$	-	-	100	μA
Total Capacitance	C_J	$V_R = 0\text{V}, f = 1.0\text{MHz}$	-	-	5	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 30\text{mA}$ $I_{rr} = 0.1 \times I_R, R_L = 100\Omega$	-	-	50	ns

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Typical Reverse Characteristic




Fig 2 Typical Forward Characteristics




Fig 3 Capacitance vs. Reverse Voltage





Fig 4 Power Derating Curve


Package Outline Dimensions (Unit: mm)



SOD-323		
Dimension	Min.	Max.
A	1.60	1.80
B	1.20	1.40
C	0.80	0.90
D	0.25	0.35
E	0.22	0.42
H	0.02	0.10
J	0.05	0.15
K	2.55	2.75

Mounting Pad Layout (Unit: mm)

SOD-323



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.