



Features

- Epitaxial planar die construction
- Two internal isolated NPN/PNP transistors in one package
- Ultra-small surface mount package

HF

Mechanical Data

- Case: SOT-363
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-363

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BC817PN	SOT-363	3000 pcs / Tape & Reel	N4

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	NPN	PNP	Unit
Collector-Base Voltage	V _{CBO}	50	-50	V
Collector-Emitter Voltage	V _{CEO}	45	-45	V
Emitter-Base Voltage	V _{EBO}	5	-5	V
Collector Current (Continuous)	I _C	0.5	-0.5	A
Collector Current (Pulse)	I _{CM}	1	-1	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	300	mW
Thermal Resistance Junction-to-Air	R _{θJA}	417	°C/W
Operating Junction Temperature	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Electrical Characteristics of NPN Transistor (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 100\mu\text{A}, I_E = 0$	50	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 10\text{mA}, I_B = 0$	45	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 100\mu\text{A}, I_C = 0$	5	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = 25\text{V}, I_E = 0$	-	-	100	nA
Emitter Cut-off Current	I_{EBO}	$V_{EB} = 5\text{V}, I_C = 0$	-	-	100	nA
DC Current Gain	h_{FE}	$V_{CE} = 1\text{V}, I_C = 100\text{mA}$	160	-	400	-
		$V_{CE} = 1\text{V}, I_C = 500\text{mA}$	40	-	-	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 500\text{mA}, I_B = 50\text{mA}$	-	-	0.7	V
Base-emitter Voltage	$V_{BE(ON)}$	$V_{CE} = 1\text{V}, I_C = 500\text{mA}$	-	-	1.2	V
Transition Frequency	f_T	$I_C = 50\text{mA}, V_{CE} = 5\text{V}$	-	170	-	MHz
Collector Output Capacitance	C_{OBO}	$V_{CB} = 10\text{V}, I_E = 0, f = 1\text{MHz}$	-	6	-	pF

Electrical Characteristics of PNP Transistor (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = -10\mu\text{A}, I_E = 0$	-50	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -10\text{mA}, I_B = 0$	-45	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = -10\mu\text{A}, I_C = 0$	-5	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = -25\text{V}, I_E = 0$	-	-	-100	nA
Emitter Cut-off Current	I_{EBO}	$V_{EB} = -5\text{V}, I_C = 0$	-	-	-100	nA
DC Current Gain	h_{FE}	$V_{CE} = -1\text{V}, I_C = -100\text{mA}$	160	-	400	-
		$V_{CE} = -1\text{V}, I_C = -500\text{mA}$	40	-	-	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -500\text{mA}, I_B = -50\text{mA}$	-	-	-0.7	V
Base-emitter Voltage	$V_{BE(ON)}$	$V_{CE} = -1\text{V}, I_C = -500\text{mA}$	-	-	-1.2	V
Transition Frequency	f_T	$I_C = -10\text{mA}, V_{CE} = -5\text{V}$	-	200	-	MHz
Collector Output Capacitance	C_{OBO}	$V_{CB} = -10\text{V}, I_E = 0, f = 1\text{MHz}$	-	-	10	pF

Ratings and Characteristic Curves-NPN (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C




Fig 4 $V_{BE(on)}$ vs. I_C

Ratings and Characteristic Curves-PNP (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C





Fig 4 $V_{BE(on)}$ vs. I_C


Package Outline Dimensions (Unit: mm)



SOT-363		
Dimension	Min.	Max.
A	2.00	2.20
B	1.15	1.35
C	0.85	1.05
D	0.15	0.35
E	0.25	0.40
G	0.60	0.70
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40

Package Outline Dimensions (Unit: mm)

SOT-363



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.