NPN Dual Small Signal Surface Mount Transistor

BC847BV


Features

HF

- Epitaxial die construction
- Complementary PNP Type Available (BC857BV)
- Ultra-small surface mount package

Mechanical Data

- Case: SOT-563
- Molding compound: UL flammability classification rating 94V-0
- Terminal s: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-563

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BC847BV	SOT-563	3000 pcs / Tape Reel	K4V

Maximum Ratings (@ T_A = 25℃ unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	50	V
Collector-Emitter Voltage	V_{CEO}	45	V
Emitter-Base Voltage	V_{EBO}	6	V
Collector Current (Continuous)	I_C	100	mA
Collector Current (Peak)	I_{CM}	200	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation *1	P_C	150	mW
Thermal Resistance (Junction-to-Ambient) *1	$R_{\theta JA}$	833	°C/W
Operating junction Temperature	T_J	-55 ~ +150	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

Electrical Characteristics (@ T_A = 25℃ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	I_C = 10μA, I_B = 0	50	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	I_C = 10mA, I_B = 0	45	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	I_E = 1μA, I_C = 0	6	-	-	V
Collector Cut-off Current	I_{CBO}	V_{CB} = 30V, I_E = 0	-	-	15	nA
Emitter-base Cut-off Current	I_{EBO}	V_{EB} = 5V, I_C = 0	-	-	100	nA
Collector-emitter Cut-off Current	I_{CEO}	V_{CE}= 30V, I_B = 0	-	-	1	mA
DC Current Gain	h_{FE}	V_{CE} = 5V, I_C = 2mA	200	-	450	-
Collector-Emitter Saturation Voltage (Note 2)	$V_{CE(sat)}$	I_C = 10mA, I_B = 0.5mA	-	-	0.25	V
		I_C = 100mA, I_B = 5mA	-	-	0.60	V
Base-Emitter Saturation Voltage (Note 2)	$V_{BE(sat)}$	I_C = 10mA, I_B = 0.5mA	-	0.7	0.90	V
		I_C = 100mA, I_B = 5mA	-	0.9	1.10	V
Base-Emitter Voltage (Note 2)	$V_{BE(ON)}$	V_{CE} = 5V, I_C= 2mA	0.58	0.66	0.70	V
		V_{CE} = 5V, I_C= 10mA	-	-	0.77	V
Transition Frequency	f_T	V_{CE} = 5V, I_C= 10mA f = 100MHz	100	-	-	-
Emitter Input Capacitance	Cib	V_{CB} = 0.5V, I_C = 0 f = 1MHz	-	13.28	-	pF
Collector Output Capacitance	Cob	V_{CB} = -10V, I_E = 0 f = 1MHz	-	1.52	-	pF

Note 1: Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch.

Ratings and Characteristic Curves (T_A=25℃ unless otherwise noted)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C





Fig 4 $V_{BE(ON)}$ vs. I_C


Package Outline Dimensions (Unit: mm)



SOT-563		
Dimension	**Min.**	**Max.**
A	1.500	1.700
B	1.100	1.300
C	0.525	0.600
D	0.170	0.270
E	0.100	0.300
G	0.450	0.550
H	0.000	0.050
J	0.090	0.160
K	1.500	1.700

Package Outline Dimensions (Unit: mm)

SOT-563



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.