



Features

- Epitaxial planar die construction
- Two internal isolated NPN/PNP transistors in one package
- Ultra-small surface mount package

HF

Mechanical Data

- Case: SOT-563
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-563

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BC847BVPN	SOT-563	3000 pcs / Tape & Reel	7P

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	NPN	PNP	Unit
Collector-Base Voltage	V _{CBO}	50	-50	V
Collector-Emitter Voltage	V _{CEO}	45	-45	V
Emitter-Base Voltage	V _{EBO}	6	-5	V
Collector Current (Continuous)	I _C	100	-100	mA
Collector Current (Pulse)	I _{CM}	200	-200	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation *1	P _D	357	mW
Thermal Resistance (Junction-to-Ambient) *1	R _{θJA}	350	°C/W
Operating Junction Temperature	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper

Electrical Characteristics of NPN Transistor (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10\mu\text{A}, I_E = 0$	50	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 10\text{mA}, I_B = 0$	45	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 1\mu\text{A}, I_C = 0$	6	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = 30\text{V}, I_E = 0$	-	-	15	nA
DC Current Gain	h_{FE}	$V_{CE} = 5\text{V}, I_C = 2\text{mA}$	200	290	450	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 10\text{mA}, I_B = 0.5\text{mA}$	-	0.09	0.25	V
		$I_C = 100\text{mA}, I_B = 5\text{mA}$	-	0.20	0.60	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 10\text{mA}, I_B = 0.5\text{mA}$	-	0.70	-	V
		$I_C = 100\text{mA}, I_B = 5\text{mA}$	-	0.90	-	V
Base-Emitter Voltage	$V_{BE(ON)}$	$V_{CE} = 5\text{V}, I_C = 2\text{mA}$	0.58	0.66	0.70	V
		$V_{CE} = 5\text{V}, I_C = 10\text{mA}$	-	-	0.72	V
Transition Frequency	f_T	$V_{CE} = 5\text{V}, I_C = 10\text{mA}$ $f = 100\text{MHz}$	100	-	-	MHz
Output Capacitance	C_{OBO}	$V_{CB} = 10\text{V}, f = 1.0\text{MHz}$	-	3.5	6.0	pF
Noise Figure	N_F	$V_{CE} = 5\text{V}, f = 1.0\text{MHz}$ $I_C = 200\text{mA}, R_G = 2\text{k}\Omega$	-	2.0	10	dB

Electrical Characteristics of PNP Transistor (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = -10\mu\text{A}, I_E = 0$	-50	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -10\text{mA}, I_B = 0$	-45	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = -1\mu\text{A}, I_C = 0$	-6	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = -30\text{V}, I_E = 0$	-	-	-15	nA
DC Current Gain	h_{FE}	$V_{CE} = -5\text{V}, I_C = -2\text{mA}$	200	290	450	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -10\text{mA}, I_B = -0.5\text{mA}$	-	-0.075	-0.3	V
		$I_C = -100\text{mA}, I_B = -5\text{mA}$	-	-0.25	-0.65	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = -10\text{mA}, I_B = -0.5\text{mA}$	-	-0.70	-	V
		$I_C = -100\text{mA}, I_B = -5\text{mA}$	-	-0.85	-0.95	V
Base-Emitter Voltage	$V_{BE(ON)}$	$V_{CE} = -5\text{V}, I_C = -2\text{mA}$	-0.6	-0.65	-0.75	V
		$V_{CE} = -5\text{V}, I_C = -10\text{mA}$	-	-	-0.82	V
Transition Frequency	f_T	$V_{CE} = -5\text{V}, I_C = -10\text{mA}$ $f = 100\text{MHz}$	100	-	-	MHz
Output Capacitance	C_{OBO}	$V_{CB} = -10\text{V}, f = 1.0\text{MHz}$	-	3	4.5	pF
Noise Figure	N_F	$V_{CE} = -5\text{V}, f = 1.0\text{MHz}$ $I_C = -200\text{mA}, R_G = -2\text{k}\Omega$	-	-	10	dB

Ratings and Characteristic Curves-NPN (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 DC current gain as a function of collector current




Fig 2 Base-emitter voltage as a function of collector current




Fig 3 Collector-emitter saturation voltage as a function of collector current




Fig 4 Base-emitter saturation voltage as a function of collector current

Ratings and Characteristic Curves-PNP (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 DC current gain as a function of collector current




Fig 2 Base-emitter voltage as a function of collector current




Fig 3 Collector-emitter saturation voltage as a function of collector current





Fig 4 Base-emitter saturation voltage as a function of collector current


Package Outline Dimensions (Unit: mm)



SOT-563		
Dimension	Min.	Max.
A	1.500	1.700
B	1.100	1.300
C	0.525	0.600
D	0.170	0.270
E	0.100	0.300
G	0.450	0.550
H	0.000	0.050
J	0.090	0.160
K	1.500	1.700

Package Outline Dimensions (Unit: mm)

SOT-563



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.