



Features

- Epitaxial planar die construction
- Complementary NPN type available BC847S
- Ultra-small surface mount package

HF

Mechanical Data

- Case: SOT-363
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-363

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BC857BS	SOT-363	3000 pcs / Tape & Reel	3C

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	-50	V
Collector-Emitter Voltage	V_{CEO}	-45	V
Emitter-Base Voltage	V_{EBO}	-5	V
Collector Current (Continuous)	I_C	-200	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation ($T_A = 25^\circ\text{C}$)	P_D	300	mW
Thermal Resistance Junction-to-Air	$R_{\theta JA}$	417	$^\circ\text{C/W}$
Operating Junction Temperature	T_J	-55 ~ +150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = -10\mu\text{A}, I_E = 0$	-50	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -10\text{mA}, I_B = 0$	-45	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = -10\mu\text{A}, I_C = 0$	-5	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = -30\text{V}, I_E = 0, T_J = 25^\circ\text{C}$	-	-	-15	nA
		$V_{CB} = -30\text{V}, I_E = 0, T_J = 150^\circ\text{C}$	-	-	-4	μA
Emitter-base Cut-off Current	I_{EBO}	$V_{EB} = -5\text{V}, I_C = 0$	-	-	-100	nA
DC Current Gain	h_{FE}	$V_{CE} = -5\text{V}, I_C = -2\text{mA}$	200	-	475	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -10\text{mA}, I_B = -0.5\text{mA}$	-	-	-0.3	V
		$I_C = -100\text{mA}, I_B = -5\text{mA}$	-	-	-0.65	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = -10\text{mA}, I_B = -0.5\text{mA}$	-	-0.70	-	V
		$I_C = -100\text{mA}, I_B = -5\text{mA}$	-	-0.85	-	V
Base-Emitter Voltage	$V_{BE(ON)}$	$V_{CE} = -5\text{V}, I_C = -2\text{mA}$	-0.6	-	-0.75	V
		$V_{CE} = -5\text{V}, I_C = -10\text{mA}$	-	-	-0.82	V
Transition Frequency	f_T	$V_{CE} = -5\text{V}, I_C = -10\text{mA}$ $f = 100\text{MHz}$	200	-	-	MHz
Collector Capacitance	C_C	$V_{CB} = -10\text{V}, I_E = I_C = 0, f = 1\text{MHz}$	-	-	3.5	pF
Noise Figure	N_F	$I_C = 0.2\text{mA}, V_{CE} = 5\text{V}, R_S = 2\text{k}\Omega$ $f = 1\text{kHz}, BW = 200\text{Hz}$	-	-	2.5	dB

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C






Fig 4 $V_{BE(on)}$ vs. I_C

Package Outline Dimensions (Unit: mm)



Package Outline Dimensions (Unit: mm)



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.