



Features

- Low leakage current
- Low capacitance characteristics
- Large dynamic range

HF

Mechanical Data

- Case: SOT-323
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-323

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BFR370F	SOT-323	3000pcs / Tape & Reel	FDs

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Breakdown Voltage	V _{CBO}	15	V
Collector-Emitter Breakdown Voltage	V _{CEO}	6	V
Emitter-Base Breakdown Voltage	V _{EBO}	2	V
Collector Current (continuous)	I _C	50	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	250	mW
Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-65 ~ +150	°C

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1\text{mA}, I_B = 0$	6	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = 6\text{V}, I_E = 0$	-	-	30	nA
Emitter Cut-off Current	I_{EBO}	$V_{EB} = 6\text{V}, I_C = 0$	-	-	500	nA
DC Current Gain	h_{FE}	$V_{CE} = 3\text{V}, I_C = 20\text{mA}$	90	120	160	-
Transition Frequency	f_T	$I_C = 20\text{mA}, V_{CE} = 3\text{V}, f = 1\text{GHz}$	11	12	-	GHz
Insertion Power Gain	$ S_{21e} ^2$	$V_{CE} = 5\text{V}, I_C = 20\text{mA}$ $f = 1.8\text{GHz}$	-	12.0	-	dB
		$V_{CE} = 5\text{V}, I_C = 20\text{mA}$ $f = 3.0\text{GHz}$	-	8.5	-	
Feed-Back Capacitance	C_{re}	$I_C = I_C = 0, V_{CB} = 5\text{V}, f = 1\text{MHz}$	-	0.22	-	pF
Collector Capacitance	C_c	$I_E = I_E = 0, V_{CB} = 5\text{V}, f = 1\text{MHz}$	-	0.4	0.5	pF
Emitter Capacitance	C_e	$I_C = I_C = 0, V_{EB} = 0.5\text{V}, f = 1\text{MHz}$	-	0.42	-	pF
Noise Figure	N_F	$V_{CE} = 3\text{V}, I_C = 3\text{mA}$ $f = 1.8\text{GHz}$	-	1.0	-	dB
Maximum Unilateral Power Gain	G_{UM}	$V_{CE} = 5\text{V}, I_C = 20\text{mA}, f = 1.8\text{GHz}$	-	13.5	-	dB
		$V_{CE} = 5\text{V}, I_C = 20\text{mA}, f = 3.0\text{GHz}$	-	10	-	
	IP_3	$V_{CE} = 3\text{V}, I_C = 20\text{mA}$ $Z_S = Z_L = 50\Omega, f = 1.8\text{GHz}$		22		dBm

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig. 1 Total Power Dissipation vs. Ambient Temperature




Fig. 2 Reverse Transfer Capacitance vs. Collector to Base Voltage




Fig. 3 Gain vs. Function of Frequency




Fig. 4 DC Current vs. Collector Current




Fig. 5 Gain vs. Function of Collector Current




Fig. 6 Gain vs. Function of Collector Current




Fig. 7 Gain vs. Function of Collector Current





Fig. 8 Noise Figure vs. Collector Current


Package Outline Dimensions (Unit: mm)



SOT-323		
Dimension	Min.	Max.
A	2.00	2.20
B	1.15	1.35
C	0.90	1.10
D	0.15	0.35
E	0.25	0.40
G	1.20	1.40
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40

Mounting Pad Layout (Unit: mm)

SOT-323



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.