
N-Channel Enhancement Mode MOSFET

BL03N10-3L

Features


- Electrostatic sensitive devices
- Excellent package for good heat dissipation

HF



APPLICATIONS

- Power switching application
- Hard switching and high frequency circuits
- Uninterruptible power supply



SOT-23-3L

Mechanical Data

- Case: SOT-23-3L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL03N10-3L	SOT-23-3L	3000 pcs / Tape & Reel	03N10

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DSS}	100	V
Gate-to-Source Voltage	V_{GSS}	±20	V
Continuous Drain Current (T_C = 25°C)	I_D	3	A
Continuous Drain Current (T_A = 25°C)	I_D	1.4	A
Continuous Drain Current (T_A = 70°C)	I_D	1.1	A
Pulsed Drain Current (t_p = 10μs, T_A = 25°C)	I_{DM}	12	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation (T_A = 25°C)	P_D	0.9	W
Thermal Resistance Junction-to-Air *1	$R_{\theta JA}$	140	°C/W
Thermal Resistance Junction-to-Case *1	$R_{\theta JC}$	50	°C/W
Operating Junction Temperature Range	T_J	-55 ~ +150	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

Electrical Characteristics (@ T_A = 25°C unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V_{DSS}	Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 250μA	100	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 100V, V_{GS} = 0V	-	-	1	μA
I_{GSS}	Gate-Body Leakage Current	V_{GS} = ±20V, V_{DS} = 0V	-	-	±100	nA
On Characteristics						
$R_{DS(ON)}$	Static Drain-Source On-resistance *2	V_{GS} = 10V,I_D = 3A	-	0.204	0.22	Ω
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250μA	1	2.1	2.5	V
g_{FS}	Forward Transconductance	V_{DS} = 5V, I_D = 2.9A	-	-	1.2	S
Dynamic Characteristics						
C_{ISS}	Input Capacitance	V_{GS} = 0V V_{DS} = 25V f = 1.0MHz	-	392	-	pF
C_{OSS}	Output Capacitance		-	24	-	
C_{RSS}	Reverse Transfer Capacitance		-	14	-	
Switching Characteristics						
$t_{d(ON)}$	Turn-on Delay Time	V_{DD} = 30V, V_{GS} = 10V R_G = 2.5Ω, R_L = 15Ω I_D = 2A	-	11	-	ns
t_r	Turn-on Rise Time		-	7.4	-	
$t_{d(OFF)}$	Turn-Off Delay Time		-	35	-	
t_f	Turn-Off Fall Time		-	9.1	-	
Q_G	Total Gate-Charge	V_{DD} = 30V V_{GS} = 10V I_D = 2A	-	12	-	nC
Q_{GS}	Gate to Source Charge		-	3	-	
Q_{GD}	Gate to Drain (Miller) Charge		-	1.6	-	
Source-Drain Diode Characteristics						
V_{SD}	Diode Forward Voltage *2	I_{SD} = 3A, V_{GS} = 0V, T_J = 25°C	-	-	1.2	V

Notes:

1. The data tested by surface mounted on a 1 inch^2 FR-4 board with 2OZ copper
2. The data tested by pulsed, pulse width ≤ 300μs, duty cycle ≤ 2%

Ratings and Characteristics Curves (@ T_A = 25°C unless otherwise specified)




Fig 1 On-Region Characteristics




Fig 2 On-Resistance vs. Drain Current and Gate Voltage




Fig 3 On-Resistance vs. Gate-Source Voltage




Fig 4 Body-Diode Characteristics




Fig 5 On-Resistance vs. Junction Temperature




Fig 6 Transfer Characteristics




Fig 7 Capacitance Characteristics




Fig 8 Drain-Source vs. Junction Temperature




Fig 9 Gate Voltage vs. Junction Temperature




Fig 10 Safe Operation Area





Fig 11 Maximum transient thermal impedance


Package Outline Dimensions (Unit: mm)



SOT-23-3L		
Dimension	**Min.**	**Max.**
A	2.80	3.00
B	1.50	1.70
C	1.00	1.20
D	0.35	0.45
E	0.35	0.55
G	1.80	2.00
H	0.02	0.10
J	0.10	0.20
K	2.60	3.00

Mounting Pad Layout (Unit: mm)

SOT-23-3L



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.