


Features

- Advanced Shielded-Gate Trench technology
- Low on-resistance
- Fast switching speed
- Low thermal resistance

HF

Mechanical Data

- Case: PDFN3×3-8L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



PDFN3×3-8L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL090N04T-3DL8	PDFN3×3-8L	5000 pcs / Tape & Reel	090N04T

Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V _{DSS}	40	V
Gate-to-Source Voltage	V _{GSS}	±20	V
Continuous Drain Current (T _C = 25°C)	I _D	45	A
Continuous Drain Current (T _C = 100°C)		28	A
Continuous Drain Current (T _A = 25°C) *1		12	A
Continuous Drain Current (T _A = 100°C) *1		7.7	A
Pulsed Drain Current (t _p = 10μs, T _C = 25°C)	I _{DM}	163	A
Single Pulse Avalanche Energy *3	E _{AS}	13	mJ
Power Dissipation (T _C = 25°C)	P _D	28	W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Case	R _{θJC}	-	4.3	4.5	°C/W
Thermal Resistance Junction-to-Air *1	R _{θJA}	-	51	61	°C/W

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	40	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 40V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *2	V _{GS} = 10V, I _D = 12A	-	7	9	mΩ
		V _{GS} = 4.5V, I _D = 10A	-	11	16	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	1	1.7	2.5	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	3.6	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V	-	694	-	pF
C _{OSS}	Output Capacitance	V _{DS} = 15V	-	150	-	
C _{RSS}	Reverse Transfer Capacitance	f = 1.0MHz	-	140	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time	V _{DD} = 30V	-	11	-	ns
t _r	Turn-on Rise Time	V _{GS} = 15V	-	61	-	
t _{d(OFF)}	Turn-Off Delay Time	I _D = 20A	-	30	-	
t _f	Turn-Off Fall Time	R _G = 3.3Ω	-	13	-	
Q _G	Total Gate-Charge	V _{DD} = 20V	-	9.8	-	nC
Q _{GS}	Gate to Source Charge	V _{GS} = 4.5V	-	1.8	-	
Q _{GD}	Gate to Drain (Miller) Charge	I _D = 12A	-	5.8	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *2	I _{SD} = 1A, V _{GS} = 0V	-	0.7	1	V
t _{rr}	Reverse Recovery Time	I _{SD} = 15A, V _{GS} = 0V	-	21	-	ns
Q _{rr}	Reverse Recovery Charge	di/dt = 100A/μs	-	8.3	-	nC

Notes:

- The data tested by surface mounted on a 1 inch² FR-4 board with 20Z copper
- The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
- The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 25V, V_{GS} = 10V, L = 0.1mH$

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current





Fig 3 Typical Output Characteristics



**Fig 4 On-Resistance vs. Drain Current
and Gate Voltage**




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature




Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature




Fig 13 Safe Operating Area





Fig 14 Maximum transient thermal impedance


Package Outline Dimensions (Unit: mm)



PDFN3x3-8L		
Dimension	Min.	Max.
A	2.90	3.10
B	2.90	3.10
C	0.65	0.85
D	0.20	0.40
E	0.00	0.10
F	0.00	0.10
G	0.55	0.75
H	0.20	0.40
I	0.70	1.10
J	0.10	0.20
K	3.15	3.45
L	0.20	0.40
M	2.35	2.55
N	1.500	1.900

Mounting Pad Layout (Unit: mm)

PDFN3x3-8L



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.