



Features

- Advanced trench cell design
- Extremely low threshold voltage
- Fast switching speed with low gate charge
- HBM: JESD22-A114-B: 1A
- RoHS compliant with Halogen-free

HF



SOT-363

Mechanical Data

- Case: SOT-363
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL1308ESDW	SOT-363	3000 pcs / Tape & Reel	KG

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DS}	30	V
Gate-to-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current ($T_A = 25^\circ\text{C}$) *1	I_D	1.4	A
Continuous Drain Current ($T_A = 70^\circ\text{C}$) *1		1.1	A
Pulsed Drain Current ($t_p = 10\mu\text{s}$, $T_A = 25^\circ\text{C}$)	I_{DM}	6	A
Single Pulse Avalanche Energy *3	E_{AS}	2	mJ

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation ($T_A = 25^\circ\text{C}$) *1	P_D	0.32	W
Thermal Resistance Junction-to-Air *1	$R_{\theta JA}$	390	$^\circ\text{C/W}$
Operating Junction Temperature Range	T_J	$-55 \sim +150$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ\text{C}$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	30	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 30V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±12V, V _{DS} = 0V	-	-	±15	μA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *2	V _{GS} = 4.5V, I _D = 0.5A	-	130	150	mΩ
		V _{GS} = 2.5V, I _D = 0.5A	-	150	180	mΩ
		V _{GS} = 1.8V, I _D = 0.5A	-	190	260	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	0.4	0.8	1	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	4.8	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = 15V f = 1.0MHz	-	171	-	pF
C _{OSS}	Output Capacitance		-	15	-	
C _{RSS}	Reverse Transfer Capacitance		-	10	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time *4	V _{DS} = 15V V _{GS} = 4.5V R _G = 10Ω I _D = 1A	-	7	-	ns
t _r	Turn-on Rise Time *4		-	12	-	
t _{d(OFF)}	Turn-Off Delay Time *4		-	13	-	
t _f	Turn-Off Fall Time *4		-	5	-	
Q _G	Total Gate-Charge	V _{DS} = 15V V _{GS} = 4.5V I _D = 0.5A	-	3.6	-	nC
Q _{GS}	Gate to Source Charge		-	0.6	-	
Q _{GD}	Gate to Drain (Miller) Charge		-	0.6	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *2	I _{SD} = 0.5A, V _{GS} = 0V	-	0.8	1.3	V

Notes:

1. The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper
2. The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
3. The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 15V, V_{GS} = 6V, L = 0.1mH$
4. Guaranteed by design, not subject to production

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Output Characteristics




Fig 2 On-Resistance vs. Drain Current and Gate Voltage




Fig 3 On-Resistance vs. Gate-Source Voltage




Fig 4 Body-Diode Characteristics




Fig 5 On-Resistance vs. Junction Temperature




Fig 6 Transfer Characteristics




Fig 7 Normalized $V_{GS(th)}$ vs. Junction Temperature




Fig 8 Normalized Breakdown Voltage vs. Junction Temperature




Fig 9 Capacitance Characteristics





Fig 10 Gate-Charge Characteristics

Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)

