


Features

- High dense cell design for extremely low $R_{DS(ON)}$
- Rugged and reliable

HF

Mechanical Data

- Case: SOT-23
- Molding Compound, UL Flammability Classification Rating 94V-0.
- Terminals: Matte Tin Plated Leads, Solderable Per MIL-STD-202, Method 208.



BL2306BD

SOT-23

Ordering Information

Part Number	Package	Shipping	Marking Code
BL2306BD	SOT-23	3000 pcs / Tape & Reel	S6

Maximum Ratings (@ $T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Units
Drain-Source Voltage	V_{DS}	30	V
Gate -Source Voltage	V_{GS}	± 20	V
Continuous Drain Current $T_A = 25^{\circ}\text{C}$ $T_A = 70^{\circ}\text{C}$	I_D (Note1,2)	3.16 2.7	A
Pulsed Drain Current ,PW ≤ 300 us, Duty Cycle $\leq 2\%$	I_{DM}	20	A
Continuous Source Current	I_S (Note1,2)	0.62	A
Power Dissipation $T_A=25^{\circ}\text{C}$ $T_A=70^{\circ}\text{C}$	P_D (Note1,2)	0.75 0.48	W

Thermal Characteristics

Parameter	Symbol	Limits	Unit
Thermal Resistance Junction to Ambient Air	$R_{\theta JA}$ (Note1)	166	$^{\circ}\text{C/W}$
Operating Junction Temperature Range	T_j	150	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150	$^{\circ}\text{C}$

Notes:

1. Surface Mounted on FR4 Board, $t \leq 5$ sec.
2. Pulse width limited by maximum junction temperature.
3. Pulse test: PW ≤ 300 us duty cycle $\leq 2\%$.

Electrical Characteristics (@T_A=25°C unless otherwise specified)

Symbol	Parameter	Test conditions	MIN	TYP	MAX	UNIT
OFF Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	30	-	-	V
I _{DSS}	Drain to Source Leakage Current	V _{DS} =30V, V _{GS} =0V V _{DS} =30V, V _{GS} =0V, T _J = 55°C	-	-	0.5 10	μA
I _{GSS}	Gate-body Leakage	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
ON Characteristics ^(Note 3)						
R _{DS(ON)}	Static Drain-Source On-resistance	V _{GS} =10V, I _D =-3.5A	-	-	0.047	Ω
		V _{GS} =4.5V, I _D =2.8A	-	-	0.065	
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D =250uA	1	-	3	V
g _{fs}	Forward Transconductance	V _{DS} =4.5 V, I _D =2.5 A	-	7	-	S
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{GS} = 0V	-	420	-	pF
C _{oss}	Output Capacitance	V _{DS} = 15V	-	60	-	
C _{rss}	Reverse Transfer Capacitance	f = 1.0MHz	-	53	-	
Q _g	Gate Charge	V _{DS} =15 V, V _{GS} =4.5 V, I _D =1 A	-	5	-	nC
Q _{gs}	Gate-Source Charge		-	1.1	-	
Q _{gd}	Gate-Drain Charge		-	2.6	-	
t _{d(on)}	Turn-On Delay Time	V _{GS} = 10V, V _{DD} = 15V R _g = 3.3Ω I _D = 1A	-	2	-	ns
t _r	Rise Time		-	34	-	
t _{d(off)}	Turn-Off Delay Time		-	13	-	
t _f	Fall Time		-	6	-	
t _{rr}	Reverse Recovery Time	I _F =5 A ,di/dt =100 A/us		8.7		ns
Q _{rr}	Body Diode Reverse Recovery Charge			2.3		nC
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage	I _S =1.25A, V _{GS} =0 V	-	0.8	1.2	V

Ratings and Characteristic Curves ($T_A=25^{\circ}\text{C}$ unless otherwise noted)




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance vs. G-S Voltage




Fig.3 Forward Characteristics of Reverse Diode




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ vs. T_J




Fig.6 Normalized $R_{DS(on)}$ vs. T_J




Fig.7 Capacitance




Fig.8 Safe Operating Area





Fig.9 Normalized Maximum Transient Thermal Impedance

Package Outline Dimensions(unit:mm)


SOT-23



SOT-23		
Dim	Min	Max
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60

Mounting Pad Layout(unit:mm)

SOT-23



IMPORTANT NOTICE

Galaxy Microelectronics (GME) reserves the right to make changes without further notice to any product herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.