


Features

- Electrostatic sensitive devices
- $R_{DS(ON)} < 26.5m\Omega$ @ $V_{GS} = 10V$
- $R_{DS(ON)} < 32m\Omega$ @ $V_{GS} = 4.5V$
- $R_{DS(ON)} < 48m\Omega$ @ $V_{GS} = 2.5V$

HF

Mechanical Data

- Case: DFN2020-6L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



DFN2020-6L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL3400DF1	DFN2020-6L	3000 pcs / Tape & Reel	3400

Maximum Ratings (@ $T_A = 25^\circ C$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DS}	30	V
Gate-to-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current ($T_A = 25^\circ C$) *1	I_D	6.6	A
Continuous Drain Current ($T_A = 70^\circ C$) *1		5.5	A
Pulsed Drain Current ($t_p = 10\mu s$, $T_A = 25^\circ C$)	I_{DM}	30	A
Single Pulse Avalanche Energy *3	E_{AS}	7	mJ
Power Dissipation ($T_A = 25^\circ C$) *1	P_D	2.4	W
Operating Junction Temperature Range	T_J	$-55 \sim +150$	$^\circ C$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ C$

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Air *1	$R_{\theta JA}$	-	-	52	$^\circ C/W$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	30	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 30V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±12V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *2	V _{GS} = 10V, I _D = 5.7A	-	18	26.5	mΩ
		V _{GS} = 4.5V, I _D = 5A	-	22	32	
		V _{GS} = 2.5V, I _D = 3A	-	40	48	
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	0.7	0.8	1.4	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	9	-	Ω
Dynamic Characteristics						
g _{FS}	Forward Transconductance	V _{DS} = 5V, I _D = 5.7A	-	26	-	S
C _{ISS}	Input Capacitance	V _{GS} = 0V	-	451	-	pF
C _{OSS}	Output Capacitance	V _{DS} = 15V	-	64	-	
C _{RSS}	Reverse Transfer Capacitance	f = 1.0MHz	-	59	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time *4	V _{GS} = 10V V _{DD} = 15V R _L = 2.6Ω R _G = 3Ω	-	3.2	-	ns
t _r	Turn-on Rise Time *4		-	3.5	-	
t _{d(OFF)}	Turn-Off Delay Time *4		-	21.5	-	
t _f	Turn-Off Fall Time *4		-	2.7	-	
Q _G	Total Gate-Charge	V _{GS} = 4.5V	-	7	-	nC
Q _{GS}	Gate to Source Charge	V _{DS} = 15V	-	1.4	-	
Q _{GD}	Gate to Drain (Miller) Charge	I _D = 5.7A	-	2.2	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *2	I _S = 1A, V _{GS} = 0 V	-	0.7	1.0	V
t _{rr}	Body Diode Reverse Recovery Time	I _{SD} = 5A, V _{GS} = 0V	-	85	-	ns
Q _{rr}	Body Diode Reverse Recovery Charge	di/dt = 100A/μs	-	50	-	nC

Notes:

- The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper
- The data tested by pulsed, pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$
- The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 15\text{V}$, $V_{GS} = 6\text{V}$, $L = 0.1\text{mH}$
- Guaranteed by design, not subject to production

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current
and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature





Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature


Package Outline Dimensions (Unit: mm)



DFN2020-6L		
Dimension	Min.	Max.
A	1.924	2.076
B	1.924	2.076
C	0.500	0.600
D	0.250	0.350
E	0.900	1.100
F	0.850	1.050
G	0.200	0.400
H	0.000	0.050
I	0.550	0.750
J	0.103	0.303
K	0.150	0.350
L	0.200	0.400
M	0.700	0.900

Mounting Pad Layout (Unit: mm)

DFN2020-6L



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.