


Features

- Electrostatic sensitive devices

HF

Mechanical Data

- Case: SOT-23
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



SOT-23

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL3402	SOT-23	3000 pcs / Tape & Reel	3402

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V _{DSS}	30	V
Gate-to-Source Voltage	V _{GSS}	±12	V
Continuous Drain Current (T _A = 25°C)	I _D	4	A
Continuous Drain Current (T _A = 70°C)		3.4	A
Pulsed Drain Current	I _{DM}	15	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	1.4	W
Thermal Resistance Junction-to-Air	R _{θJA}	70	°C/W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	30	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 24V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±12V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Static Drain-Source On-resistance	V _{GS} = 10V, I _D = 4A	-	31	55	mΩ
		V _{GS} = 4.5V, I _D = 3A	-	33	70	
		V _{GS} = 2.5V, I _D = 2A	-	42	110	
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	0.6	0.83	1.4	V
g _{FS}	Forward Transconductance	V _{DS} = 5V, I _D = 4A	-	8	-	S
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = 15V f = 1.0MHz	-	850	-	pF
C _{OSS}	Output Capacitance		-	80	-	
C _{RSS}	Reverse Transfer Capacitance		-	71	-	
R _G	Gate Resistance	V _{DS} = 0V, V _{GS} = 0V f = 1.0MHz	-	2.4	-	Ω
Switching Characteristics						
Q _G	Total Gate-Charge	V _{GS} = 10V V _{DS} = 15V I _D = 4A	-	24	-	nC
Q _{GS}	Gate to Source Charge		-	1.8	-	
Q _{GD}	Gate to Drain (Miller) Charge		-	3.7	-	
t _{d(ON)}	Turn-on Delay Time	V _{GS} = 10V V _{DD} = 15V R _L = 3.75Ω R _G = 6Ω	-	3.3	-	ns
t _r	Turn-on Rise Time		-	1	-	
t _{d(OFF)}	Turn-Off Delay Time		-	21.7	-	
t _f	Turn-Off Fall Time		-	2.1	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage	I _S = 2A, V _{GS} = 0 V	-	0.68	1.0	V
t _{rr}	Body Diode Reverse Recovery Time	I _F = 4A, dI/dt = 100A/μs	-	90	-	nS
Q _{rr}	Body Diode Reverse Recovery Charge		-	56	-	nC

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Output Characteristics




Fig 2 On-Resistance vs. Drain Current and Gate Voltage




Fig 3 On-Resistance vs. Gate-Source Voltage




Fig 4 Body-Diode Characteristics




Fig 5 On-Resistance vs. Junction Temperature




Fig 6 Transfer Characteristics




Fig 7 Capacitance Characteristics




Fig 8 Gate Voltage vs. Junction Temperature




Fig 9 Drain-Source vs. Junction Temperature





Fig 10 Gate Threshold Voltage vs.
Junction Temperature


Package Outline Dimensions (Unit: mm)



SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.