




## SILICON BIDIRECTIONAL DIACS

VOLTAGE RANGE: 28-45 V

### FEATURES

- ◇ The three layer,two terminal,axial lead,hermetically sealed diacs are designed specifically for triggering thyristors.They demonstrate low breakover current at breakover voltage as they withstand peak pulse current,The breakover symmetry is within three volts(DB3,DB4). These diacs are intended for use in thyristors phase control,circuits for lamp dimming, universal motor speed control,and heat control.

### DO-35(GLASS)



Dimensions in millimeters

### ABSOLUTE RATINGS

| Parameters                                                                  | Symbols   | DB3,DB4     | UNITS              |
|-----------------------------------------------------------------------------|-----------|-------------|--------------------|
| Power dissipation on printed<br>$T_A=50^{\circ}\text{C}$ circuit (L=10mm)   | $P_c$     | 150.0       | mW                 |
| Repetitive peak on-state current<br>$t_p=20\mu\text{S}$<br>$f=120\text{Hz}$ | $I_{TRM}$ | 2.0         | A                  |
| Operating junction temperature                                              | $T_J$     | -40--- +125 | $^{\circ}\text{C}$ |
| Storage temperature                                                         | $T_{STG}$ | -40--- +125 | $^{\circ}\text{C}$ |

### ELECTRICAL CHARACTERISTICS

| Parameters                         |                                | Test Conditions                                              |     | DB3       | DB4 | UNITS         |
|------------------------------------|--------------------------------|--------------------------------------------------------------|-----|-----------|-----|---------------|
| Breakover voltage (NOTE 1)         | $V_{BO}$                       | C=22nf(NOTE 2)<br>See FIG.1                                  | Min | 28        | 35  | V             |
|                                    |                                |                                                              | Typ | 32        | 40  |               |
|                                    |                                |                                                              | Max | 36        | 45  |               |
| Breakover voltage symmetry         | $I+V_{BO}$ I-<br>I- $V_{BO}$ I | C=22nf(NOTE 2)<br>See FIG.1                                  | Max | $\pm 3.0$ |     | V             |
| Dynamic breakover voltage (NOTE 1) | $I \pm \Delta V$               | $\Delta I=(I_{BO} \text{ to } I_F=10\text{mA})$<br>See FIG.1 | Min | 5.0       |     | V             |
| Output voltage (NOTE 1)            | $V_o$                          | See FIG.2                                                    | Min | 5.0       |     | V             |
| Breakover current (NOTE 1)         | $I_{BO}$                       | C=22nf(NOTE 2)                                               | Max | 100.0     |     | $\mu\text{A}$ |
| Rise time (NOTE 1)                 | $t_r$                          | See FIG.3                                                    | Typ | 1.5       |     | $\mu\text{S}$ |
| Leakage current (NOTE 1)           | $I_R$                          | $V_R=0.5 V_{BO}$<br>See FIG.1                                | Max | 10.0      |     | $\mu\text{A}$ |

NOTE: 1.Electrical characteristics applicable in both forward and reverse directions.

www.gmesemi.com

2.Connected in parallel with the devices

FIG.1--VOLTAGE-CURRENT CHARACTERISTIC CURVE




FIG.2--TEST CIRCUIT FOR OUTPUT VOLTAGE




FIG.3-- TEST CIRCUIT SEE FIG.2 ADJUST R FOR  $I_P=0.5\text{A}$




FIG.4--POWER DISSIPATION VERSUS AMBIENT TEMPERATURE (MAXIMUM VALUES)




FIG.5--RELATIVE VARIATION OF  $V_{BO}$  VERSUS JUNCTION TEMPERATURE(TYPICAL VALUES)




FIG.6--PEAK PULSEE CURRENT VERENT VERSUS PULSE DURATION(MAXIMUM VALUES)

