


Features

- Two DTC143Z chip in SOT-563 Package
- Transistor elements are independent, eliminating interference
- Mounting cost and area can be cut in half

Mechanical Data

- Case: SOT-563
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
EMH25	SOT-563	3000 pcs / Tape & Reel	H25

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Symbol	Parameter	Value		Unit
		Tr1	Tr2	
V _{CC}	Supply Voltage	50	50	V
V _{IN}	Input Voltage	-5 to +30	-5 to +30	V
I _O	Output Current	100	100	mA
I _{C(MAX.)}	Collector Current	100	100	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	150	mW
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Electrical Characteristics-TR1 and TR2 (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Input Voltage	$V_{I(off)}$	$V_{CC} = 5V, I_O = 100\mu A$	0.5	-	-	V
	$V_{I(on)}$	$V_O = 0.3V, I_O = 5mA$	-	-	1.3	V
Output Voltage	$V_{O(on)}$	$I_O = 5mA, I_I = 0.25mA$	-	0.1	0.3	V
Input Current	I_I	$V_I = 5V$	-	-	1.8	mA
Output Current	$I_{O(off)}$	$V_{CC} = 50V, V_I = 0V$	-	-	0.5	μA
DC Current Gain	G_I	$V_O = 5V, I_O = 10mA$	80	-	-	-
Input Resistor	R_I		3.29	4.7	6.11	$k\Omega$
Resistance Ratio	$R2/R1$		8	10	12	
Gain-Bandwidth Product	f_T	$V_{CE} = 10V, I_E = -5mA,$ $f = 100MHz$	-	250	-	MHz

Ratings and Characteristics Curves-TR1 and TR2 (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig. 1 Derating Curve




Fig. 2 $V_{CE(SAT)}$ vs. I_C




Fig. 3 DC Current Gain




Fig. 4 Output Capacitance




Fig. 5 Collector Current Vs. Input Voltage





Fig. 6 Input Voltage vs. Collector Current


Package Outline Dimensions (Unit: mm)



SOT-563		
Dimension	Min.	Max.
A	1.500	1.700
B	1.100	1.300
C	0.525	0.600
D	0.170	0.270
E	0.100	0.300
G	0.450	0.550
H	0.000	0.050
J	0.090	0.160
K	1.500	1.700

Package Outline Dimensions (Unit: mm)

SOT-563



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.