


Features

- Advanced trench technology
- High-speed switching
- Low threshold voltage
- HBM: JESD22-A114-B: 1A
- RoHS compliant with Halogen-free

HF

Mechanical Data

- Case: DFN2020-6LC
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



DFN2020-6LC

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
GBLP2201DF2	DFN2020-6LC	3000 pcs / Tape & Reel	P2201

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V _{DSS}	-20	V
Gate-to-Source Voltage	V _{GSS}	±12	V
Continuous Drain Current (T _A = 25°C) *1	I _D	-3.2	A
Continuous Drain Current (T _A = 70°C) *1		-2.5	
Pulsed Drain Current (t _p ≤ 10μs, T _A = 25°C)	I _{DM}	-12	A
Single Pulse Avalanche Energy *4	E _{AS}	4	mJ
Power Dissipation (T _A = 25°C) *1	P _D	1.25	W
Power Dissipation (T _A = 25°C) *2		0.5	
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Air *1	R _{θJA}	-	-	100	°C/W
Thermal Resistance Junction-to-Air *2		-	-	250	°C/W

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = -250μA	-20	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = -20V, V _{GS} = 0V	-	-	-1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±8V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *3	V _{GS} = -4.5V, I _D = -2.8A	-	50	100	mΩ
		V _{GS} = -2.5V, I _D = -2A	-	70	135	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = -250μA	-0.5	-0.7	-1.0	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	27	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = -15V f = 1.0MHz	-	538	-	pF
C _{OSS}	Output Capacitance		-	62	-	
C _{RSS}	Reverse Transfer Capacitance		-	55	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time *5	V _{DD} = -10V V _{GS} = -4.5V I _D = -1A R _G = 10Ω	-	11	-	ns
t _r	Turn-on Rise Time *5		-	35	-	
t _{d(OFF)}	Turn-Off Delay Time *5		-	30	-	
t _f	Turn-Off Fall Time *5		-	10	-	
Q _G	Total Gate-Charge	V _{DD} = -10V V _{GS} = -4.5V I _D = -3.6A	-	6.5	-	nC
Q _{GS}	Gate to Source Charge		-	1.6	-	
Q _{GD}	Gate to Drain (Miller) Charge		-	1.4	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *3	I _{SD} = -0.3A, V _{GS} = 0V	-	-0.65	-1.2	V

Notes:

1. The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper
2. The data tested by surface mounted on a minimum recommended FR-4 board
3. The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
4. The E_{AS} data shows Max. rating. The test condition is $V_{DD} = -10V, V_{GS} = -6V, L = 0.1mH$
5. Guaranteed by design, not subject to production

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature





Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature

Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)

