


Schottky Barrier Rectifier

GVS38BF - GVS310BF

Features

- Metal silicon junction, majority carrier conduction
- High forward surge current capability
- Low forward voltage drop
- High temperature soldering guaranteed: 260°C @ 10s
- Robust guarding for over voltage protection
- RoHS compliant with Halogen-free



Mechanical Data

- Case: SMBF molded plastic
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Matte tin plated leads; solderable per J-STD-002 and JESD22-B102
- Polarity: Color band denotes cathode end

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	GVS38BF	GVS39BF	GVS310BF	Unit
Peak Repetitive Reverse Voltage	V _{RRM}	80	90	100	V
RMS Reverse Voltage	V _{RMS}	56	63	70	V
DC Blocking Voltage	V _{DC}	80	90	100	V
Maximum Average Forward Output Current	I _{F_AV}	3.0			A
Peak Forward Surge Current, 8.3ms Single Half Sine wave	I _{FSM}	80			A

Thermal Characteristics

Parameter	Symbol	GVS38BF	GVS39BF	GVS310BF	Unit
Typical Thermal Resistance *1	R _{θJA}	65			°C/W
	R _{θJC}	16			
	R _{θJL}	15			
Operating Junction Temperature Range	T _J	-55 ~ +150			°C
Storage Temperature Range	T _{STG}	-55 ~ +150			°C

Note *1: Device mounted on p.c.b. with 10 mm x 20 mm x 0.1 mm copper pad area

Schottky Barrier Rectifier**GVS38BF - GVS310BF****Electrical Characteristics** (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions		Typ.	Max.	Unit
Maximum Instantaneous Forward Voltage ^{*1}	V_F	$I_F = 3.0\text{A}$	@ $T_A = 25^\circ\text{C}$	-	0.7	V
Maximum Reverse Current ^{*2}	I_R	Rated V_R	@ $T_J = 25^\circ\text{C}$	-	250	μA
			@ $T_J = 100^\circ\text{C}$	-	20	mA

Note^{*1}: Pulse test: 300us pulse width, 1 % duty cycleNote^{*2}: Pulse test: Pulse width 40ms

Schottky Barrier Rectifier

GVS38BF - GVS310BF

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Surge Current Derating Curve




Fig.3 Typical Forward Voltage Characteristics






Fig.4 Typical Reverse Characteristics




Schottky Barrier Rectifier

GVS38BF - GVS310BF

Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)



Ordering Information

Part Number	Marking	Package	Shipping Quantity
GVS38BF	VS38BF	SMBF	4000 / Tape & Reel
GVS39BF	VS39BF	SMBF	4000 / Tape & Reel
GVS310BF	VS3ABF	SMBF	4000 / Tape & Reel