

Silicon Epitaxial Planar Transistor **M8550**

FEATURES

HF

- High Collector Current. (I_C= -800 mA).
- Complementary To M8050.
- Excellent H_{FE} Linearity.
- RoHS compliant with Halogen-free





SOT-23

APPLICATIONS

- High Collector Current.

ORDERING INFORMATION

Type No.	Marking	Package Code
M8550-L	Y21	SOT-23
M8550-H	Y21	SOT-23

MAXIMUM RATING @ Ta=25℃ unless otherwise specified

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	-40	V
V_{CEO}	Collector-Emitter Voltage	-25	V
V_{EBO}	Emitter-Base Voltage	-6	V
I_C	Collector Current -Continuous	-800	mA
P_C	Collector Dissipation	200	mW
T_J, T_{STG}	Junction and Storage Temperature	-55 to +150	℃

Silicon Epitaxial Planar Transistor **M8550**

ELECTRICAL CHARACTERISTICS @ Ta=25℃ unless otherwise specified

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=-100μA,I_E=0	-40		V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=-0.1mA,I_B=0	-25		V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=-100μA,I_C=0	-6		V
Collector cut-off current	I_{CBO}	V_{CB}=-35V,I_E=0		-0.1	μA
Collector cut-off current	I_{CEO}	V_{CE}=-20V,I_B=0		-0.1	μA
DC current gain	h_{FE}	V_{CE}=-1V,I_C=-5mA	45		
		V_{CE}=-1V,I_C=-100mA	85	300	
		V_{CE}=-1V,I_C=-800mA	40		
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=-800 mA, I_B=-80mA		-0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=-800 mA, I_B=-80mA		-1.2	V
Transition frequency	f_T	V_{CE}=-6V, I_C= -20mA f=30MHz	150		MHz


CLASSIFICATION OF $h_{FE(1)}$

Rank	L	H
Range	85-200	200-300

Silicon Epitaxial Planar Transistor **M8550**


PACKAGE OUTLINE

Plastic surface mounted package SOT-23



SOT-23		
Dim	Min	Max
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60
All Dimensions in mm		

SOLDERING FOOTPRINT



Unit: mm

PACKAGE INFORMATION

Device	Package	Shipping
M8550	SOT-23	3000pcs / Tape & Reel