



Features

- Epitaxial planar die construction
- Complementary PNP type available(MMBTA55-3L)

HF

Mechanical Data

- Case: SOT-23-3L
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-23-3L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
MMBTA05-3L	SOT-23-3L	3000 pcs / Tape & Reel	1H

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V _{CBO}	60	V
Collector-Emitter Breakdown Voltage	V _{CEO}	60	V
Emitter-Base Breakdown Voltage	V _{EBO}	4	V
Collector Current (Continuous)	I _C	0.5	A
Collector Current (Peak)	I _{CM}	1	A
Base Current	I _B	0.2	A

Thermal Characteristics





Parameter	Symbol	Value	Unit
Power Dissipation	P _D	0.35	W
Thermal Resistance Junction-to-Air *1	R _{θJA}	258	°C/W
Thermal Resistance Junction-to-Case *1	R _{θJC}	142	°C/W
Thermal Resistance Junction-to-Lead *1	R _{θJL}	186	°C/W
Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 15mm * 15mm * 1mm FR4-epoxy P.C.B


Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 100\mu\text{A}$, $I_E = 0$	60	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1\text{mA}$, $I_B = 0$	60	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10\mu\text{A}$, $I_C = 0$	4	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = 60\text{V}$, $I_E = 0$	-	-	100	nA
Collector Cut-off Current	I_{CES}	$V_{CE} = 60\text{V}$, $I_B = 0$	-	-	100	nA
DC Current Gain	h_{FE}	$V_{CE} = 1\text{V}$, $I_C = 10\text{mA}$	100	-	-	-
		$V_{CE} = 1\text{V}$, $I_C = 100\text{mA}$	100	-	-	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 100\text{mA}$, $I_B = 10\text{mA}$	-	-	0.25	V
Base-emitter Voltage	$V_{BE(ON)}$	$I_C = 100\text{mA}$, $V_{CE} = 1\text{V}$	-	-	1.20	V
Current-Gain— Bandwidth Product	f_T	$I_C = 20\text{mA}$, $V_{CE} = 5\text{V}$ $f = 20\text{MHz}$	100	-	-	MHz


Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)



Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.