


Features

- ESD / transient protection of high speed data lines
 - IEC 61000-4-2 (ESD): ± 30 kV (air), ± 30 kV (contact)
- ESD rating of Class 3B (> 16 kV) per the human body model
- Low leakage

HF




Typical Applications

- Transient overvoltage protection capability

Mechanical Data

- Case: SOT-23
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



SOT-23

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
MMBZ18VAL	SOT-23	3000 pcs / Tape & Reel	18A

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Characteristic	Symbol	Value	Unit
Peak Power Dissipation ($t_p = 1.0\text{ms}$)	P_{PK}	40	W

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation ^{*1}	P_D	300	mW
Thermal Resistance Junction-to-Air ^{*1}	$R_{\theta JA}$	417	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Case ^{*1}	$R_{\theta JC}$	282	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Lead ^{*1}	$R_{\theta JL}$	252	$^\circ\text{C/W}$
Operating Junction Temperature Range	T_J	$-55 \sim +150$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ\text{C}$

Note 1: The data tested by surface mounted on a 15mm * 15mm * 1mm FR4-epoxy P.C.B

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Stand-off Voltage	V_{RWM}		-	-	14.5	V
Reverse Breakdown Voltage	$V_{(BR)}$	$I_T = 1\text{mA}$	17.10	18.00	18.90	V
Reverse Leakage Current	I_R	$V_{RWM} = 14.5\text{V}$	-	-	50	nA
Forward Voltage	V_F	$I_F = 10\text{mA}$	-	-	0.9	V
Clamping Voltage	V_{CC}	$I_{PP} = 1.6\text{A}$	-	-	25	V

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Derating Curve




Fig 2 Typical Breakdown Voltage vs. Temperature




Fig 3 Typical Leakage Current vs. Temperature




Fig 4 Typical Forward Voltage vs. Temperature




Fig 5 Junction Capacitance vs. Reverse Voltage




Fig 6 Clamping Voltage vs. Peak Pulse Current




Fig 7 Pulse Waveform





Fig 8 Pulse Derating Curve


Package Outline Dimensions (Unit: mm)



SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.9	1.1
D	0.3	0.5
E	0.35	0.48
G	1.80	2.00
H	0.02	0.1
J	0.05	0.15
K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.