



Features

- Ultra low-profile package well suited for automated assembly
- Moisture sensitivity level 1

HF

Mechanical Data

- Case: SOD-323
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



SOD-323

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
PDZ5.6B	SOD-323	3000 pcs / Tape & Reel	Z9

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation *1	P_D	400	mW
Continuous Forward Current	I_F	200	mA
Thermal Resistance Junction-to-Air	$R_{\theta JA}$	312	°C/W
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	166	°C/W
Thermal Resistance Junction-to-Lead	$R_{\theta JL}$	135	°C/W
Operating Junction Temperature Range	T_J	-55 ~ +150	°C
Storage Temperature Range	T_{STG}	-65 ~ +150	°C

Note 1: Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Zener Voltage	V_Z	$I_{ZT} = 5\text{mA}$	5.48	-	5.73	V
Forward Voltage	V_F	$I_F = 10\text{mA}$	-	-	0.9	V
		$I_F = 100\text{mA}$	-	-	1.1	V
Maximum Reverse Current	I_R	$V_R = 2.5\text{V}$	-	-	1	μA
Maximum Zener Impedance	Z_{ZT}	$I_{ZT} = 5\text{mA}$	-	-	50	Ω
Maximum Zener Impedance	Z_{ZK}	$I_{ZK} = 0.5\text{mA}$	-	-	100	Ω
Temperature Coefficient	T_C	$I_{ZT} = 5\text{mA}$	-	1.9	-	mV/°C
Diode Capacitance	C_J	$V_R = 0\text{V}, f = 1\text{MHz}$	-	-	275	pF

TYPICAL CHARACTERISTICS (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Steady State Power Derating




Fig 2 Typical Zener Breakdown Characteristics




Fig 3 Zener Impedance vs. Zener Current




Fig 4 Typical Forward Characteristics





Fig 5 Typical Reverse Characteristics


Package Outline Dimensions (Unit: mm)



SOD-323		
Dimension	Min.	Max.
A	1.60	1.80
B	1.20	1.40
C	0.80	0.90
D	0.25	0.35
E	0.22	0.42
H	0.02	0.10
J	0.05	0.15
K	2.55	2.75

Mounting Pad Layout (Unit: mm)

SOD-323



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.