

Features

- High reliability
- Small surface mounting type
- Low reverse current and low forward voltage



HF

Application

- Low current rectification

Mechanical Data

- Case: DFN0603-2L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



DFN0603-2L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
RB751LP3-40	DFN0603-2L	10000 pcs / Tape & Reel	5

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	41	V
DC Reverse Voltage	V_R	40	V
Maximum Average Forward Output Current	$I_{F(AV)}$	30	mA
Peak Forward Surge Current (8.3ms single half sine-wave)	I_{FSM}	0.5	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	100	mW
Thermal Resistance Junction-to-Air	$R_{\theta ja}^{*1}$	1000	$^\circ\text{C/W}$
Operating junction Temperature	T_J	-55 ~ +125	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-40 ~ +150	$^\circ\text{C}$





Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F^{*2}	$I_F = 1\text{mA}$	-	-	0.37	V
Maximum Peak Reverse Current	I_R^{*3}	$V_R = 30\text{V}$	-	-	0.5	μA
Typical Junction Capacitance	C_J	$V_R = 1\text{V}, f = 1\text{MHz}$	-	1.2	-	pF


Notes:

1. Part mounted on FR-4 board with recommended pad layout
2. Pulse width $\leq 380\mu\text{s}$, Duty cycle $< 2\%$
3. pulse test, $t_p \leq 5\text{ms}$

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Package Outline Dimensions (Unit: mm)



DFN0603-2L			
Dimension	Min.	Typ.	Max.
A	0.595	0.620	0.645
B	0.270	0.300	0.350
C	0.295	0.320	0.345
D	0.190	0.240	0.290
E	0.140	0.190	0.240
F	-	0.355	-
H	0	0.020	0.030

Mounting Pad Layout (Unit: mm)

DFN0603-2L



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.