


Features


- Fast switching speed
- High conductance
- RoHS compliant with Halogen-free

HF



Mechanical Data

- Case: SOT-23
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



SOT-23

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
S02JC	SOT-23	3000 pcs / Tape & Reel	S02J

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Repetitive Peak Reverse Voltage	V _{RRM}	600	V
RMS Voltage	V _{RMS}	420	V
DC Blocking Voltage	V _R	600	V
Average Rectified Output Current	I _F	0.2	A
Non-repetitive Peak Forward Surge Current, t _p = 8.3ms	I _{FSM}	5	A


Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation (T _A = 25°C)	P _D	350	mW
Thermal Resistance Junction-to-Air	R _{θJA}	357	°C/W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C


Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 100\mu\text{A}$	600	-	-	V
Forward Voltage	V_F	$I_F = 0.2\text{A}$	-	-	1.2	V
Maximum Peak Reverse Current	I_R	$V_R = 600\text{V}$	-	-	10	μA

Package Outline Dimensions (Unit: mm)

	SOT-23		
	Dimension	Min.	Max.
	A	2.70	3.10
	B	1.10	1.50
	C	0.9	1.1
	D	0.3	0.5
	E	0.35	0.48
	G	1.80	2.00
	H	0.02	0.1
	J	0.05	0.15
	K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23 
--