



Features

- Planar passivated chips
- Ultra low leakage reverse current
- High temperature performance
- High surge current capability
- RoHS compliant with Halogen-free

HF



SOD-323HE

Mechanical Data

- Case: SOD-323HE
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Marking Code
S10DHE	SOD-323HE	S1D
S10GHE	SOD-323HE	S1G
S10JHE	SOD-323HE	S1J

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	S10DHE	S10GHE	S10JHE	Unit
Peak Repetitive Reverse Voltage	V _{RRM}	200	400	600	V
RMS Reverse Voltage	V _{RMS}	140	280	420	V
DC Blocking Voltage	V _{DC}	200	400	600	V
Average Forward Output Current	I _{F(AV)}	1.0			A
Peak Forward Surge Current, 8.3ms Single Half Sine wave	I _{FSM}	20			A

Thermal Characteristics

Parameter	Symbol	S10DHE	S10GHE	S10JHE	Unit
Thermal Resistance Junction-to-Air *1	R _{θJA}	88			°C/W
Thermal Resistance Junction-to-Case *1	R _{θJC}	35			°C/W
Thermal Resistance Junction-to-Lead *1	R _{θJL}	22			°C/W
Operating Junction Temperature Range	T _J	-55 ~ +150			°C
Storage Temperature Range	T _{STG}	-55 ~ +150			°C

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R = 2\mu\text{A}$, S10DHE	200	-	-	V
		$I_R = 2\mu\text{A}$, S10GHE	400	-	-	V
		$I_R = 2\mu\text{A}$, S10JHE	600	-	-	V
Forward Voltage *2	V_F	$I_F = 1.0\text{A}$	-	-	1.1	V
Maximum Peak Reverse Current *3	I_R	Rated V_R , $T_J = 25^\circ\text{C}$	-	-	2	μA
		Rated V_R , $T_J = 125^\circ\text{C}$	-	-	50	μA
Diode capacitance	C_J	$V_R = 4\text{V}$, $f = 1\text{MHz}$	-	3.5	-	pF

Notes:

1. The data tested by surface mounted on p.c.b. with 10 mm x 20 mm x 0.1 mm copper pad area
2. The data tested by pulsed, pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 1\%$
3. The data tested by pulsed, pulse width $\leq 40\text{ms}$

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Typical Reverse Characteristic




Fig 2 Typical Forward Characteristics




Fig 3 Capacitance vs. Reverse Voltage




Fig 4 Forward Current Derating Curve





Fig 5 Surge Current Derating Curve

Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)

