

Features

- Low reverse current and low forward voltage
- High reliability
- Small surface mounting type

HF

1 2
CATHODE ANODE



SOD-123

Typical Applications

- For general purpose applications

Mechanical Data

- Case: SOD-123
- Molding compound, UL flammability classification rating 94V-0
- Terminals: Tin plated leads, solderable per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping	Marking Code
SD103AW	SOD-123	3000/Tape Reel	S4
SD103BW	SOD-123	3000/Tape Reel	S5
SD103CW	SOD-123	3000/Tape Reel	S6

Maximum Ratings (@T_A=25°C unless otherwise specified)

Characteristic	Symbol	SD103AW	SD103BW	SD103CW	Units
Peak repetitive reverse voltage	V _{RRM}	40	30	20	V
RMS Reverse voltage	V _{RMS}	28	21	14	V
Maximum average forward output current	I _{F(AV)}	350			mA
Peak forward surge current, 8.3ms single half-sine-wave	I _{FSM}	2			A

Thermal Characteristics

Characteristic	Symbol	Value	Units
Power dissipation	P _D	400	mW
Thermal Resistance Junction-to-Air	R _{θJA} *	250	°C/W
Thermal Resistance Junction-to-Case	R _{θJC} *	138	°C/W
Operating junction temperature range	T _J	125	°C
Storage temperature range	T _{STG}	-55 to +150	°C

* Part mounted on FR-4 board with recommended pad layout





Electrical Characteristics (@ $T_A=25^{\circ}\text{C}$ unless otherwise specified)

Characteristic	Symbol	Test conditions	Min.	Typ.	Max.	Units
Forward Voltage	V_F^*	$I_F=20\text{mA}$	-	-	0.37	V
		$I_F=200\text{mA}$	-	-	0.60	
Maximum Peak Reverse Current	I_R^{**}	$V_R=30\text{V}$ (SD103AW) $V_R=20\text{V}$ (SD103BW) $V_R=10\text{V}$ (SD103CW)	-	-	5	μA
Capacitance between terminals	C_T	$V_R=0\text{V}, f=1\text{MHz}$	-	22	50	pF
Reverse Recovery Time	t_{rr}	$I_F=I_R=200\text{mA}$, $I_{rr}=0.1\times I_R, R_L=100\Omega$	-	10	-	ns

*Pulse width $\leq 380\text{ }\mu\text{s}$, Duty cycle $< 2\%$


**pulse test , $t_p \leq 5\text{ms}$

Ratings and Characteristic Curves ($T_A=25^{\circ}\text{C}$ unless otherwise noted)



Package Outline Dimensions(unit:mm)


SOD-123



SOD-123		
Dim	Min	Max
A	1.45	1.75
B	2.55	2.85
C	1.00	1.30
D	0.50	0.60
E	0.25	0.45
H	0.02	0.10
J	0.05	0.15
K	3.55	3.85

Mounting Pad Layout (unit:mm)

SOD-123



IMPORTANT NOTICE

Galaxy Microelectronics (GME) reserves the right to make changes without further notice to any product herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.