

Features

- Low power loss by high speed switching and low on-resistance
- Excellent thermal behavior
- Product validation acc. JEDEC Standard
- HBM: JESD22-A114-B: 1B



HF

Applications

- PFC power supply stages
- Lighting applications
- Adapter

Mechanical Data

- Case: TO-220AB, TO-263, ITO-220AB
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



TO-220AB TO-263 ITO-220AB

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
SJ60R280	TO-220AB	50 pcs / Tube	SJ60R280
SJ60R280B	TO-263	50 pcs / Tube or 800 pcs / Tape & Reel	SJ60R280B
SJ60R280F	ITO-220AB	50 pcs / Tube	SJ60R280F

Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DSS}	600	V
Gate-to-Source Voltage	V_{GSS}	± 30	V
Continuous Drain Current ($T_C = 25^\circ\text{C}$)	I_D	15	A
Continuous Drain Current ($T_C = 100^\circ\text{C}$)		9.5	A
Pulsed Drain Current ($t_p = 10\mu\text{s}$, $T_C = 25^\circ\text{C}$)	I_{DM}	60	A
Single Pulse Avalanche Energy ^{*2}	E_{AS}	200	mJ
Power Dissipation (TO-220AB, $T_C = 25^\circ\text{C}$)	P_D	125	W
Power Dissipation (TO-263, $T_C = 25^\circ\text{C}$)		125	W
Power Dissipation (ITO-220AB, $T_C = 25^\circ\text{C}$)		42	W
Operating Junction Temperature Range	T_J	$-55 \sim +150$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Case (TO-220AB, TO-263)	$R_{\theta JC}$	-	-	1	$^{\circ}\text{C/W}$
Thermal Resistance Junction-to-Case (ITO-220AB)		-	2.3	3	$^{\circ}\text{C/W}$
Thermal Resistance Junction-to-Air (TO-220AB, TO-263)	$R_{\theta JA}$	-	-	50	$^{\circ}\text{C/W}$
Thermal Resistance Junction-to-Air (ITO-220AB)		-	-	62.5	$^{\circ}\text{C/W}$







Electrical Characteristics (@ $T_A = 25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	600	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 600V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±30V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *1	V _{GS} = 10V, I _D = 5A	-	0.24	0.28	Ω
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	2	3.2	4	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	3.1	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V	-	780	-	pF
C _{OSS}	Output Capacitance	V _{DS} = 40V	-	70	-	
C _{RSS}	Reverse Transfer Capacitance	f = 250kHz	-	2.8	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time	V _{DD} = 480V	-	20	-	ns
t _r	Turn-on Rise Time	V _{GS} = 15V	-	33	-	
t _{d(OFF)}	Turn-Off Delay Time	I _D = 8A	-	35	-	
t _f	Turn-Off Fall Time	R _G = 3.3 Ω	-	36	-	
Q _G	Total Gate-Charge	V _{DD} = 480V	-	19.7	-	nC
Q _{GS}	Gate to Source Charge	V _{GS} = 10V	-	2.5	-	
Q _{GD}	Gate to Drain (Miller) Charge	I _D = 8A	-	6.5	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *1	I _{SD} = 8A, V _{GS} = 0V	-	0.85	1.2	V
t _{rr}	Reverse Recovery Time	I _F = 5A, V _R = 400V	-	218	-	ns
Q _{rr}	Reverse Recovery Charge	di/dt = 100A/μs	-	1.8	-	μC

Notes:

- The data tested by pulsed, pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$
- The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 100\text{V}, V_{GS} = 15\text{V}, L = 50\text{mH}$

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)






Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature




Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature




Fig 13 Safe Operating Area (ITO-220AB)






Fig 14 Maximum transient thermal impedance
(ITO-220AB)


Package Outline Dimensions (Unit: mm)



TO-220AB		
Dimension	Min.	Max.
A	9.80	10.30
B	8.70	9.10
C	4.37	4.77
D	1.07	1.47
E	2.64	2.84
F	13.14	13.74
G	2.44	2.64
H	28.03	28.83
I	3.50	4.00
J	0.28	0.48
K	1.22	1.32
L	0.71	0.91
M	2.40	2.60
N	3.76	3.96




ITO-220AB		
Dimension	Min.	Max.
A	9.90	10.30
B	14.80	15.20
C	4.30	4.70
D	2.50	2.90
E	2.80	3.30
F	13.00	13.60
G	3.10	3.30
H	28.00	28.60
I	7.90	8.90
J	0.40	0.60
L	0.70	0.90
M	1.30	1.50
N	2.60	2.80
O	2.60	3.10
P	2.45	2.65
K/R	1.10	1.30



TO-263		
Dimension	Min.	Max.
A	6.00	8.00
B	9.90	10.30
C	8.50	9.10
D	4.37	4.77
E	1.07	1.47
F	1.07	1.47
G	5.34	5.74
H	2.44	2.64
J	15.30	15.90
K	0.28	0.48
L	1.17	1.37
M	0.71	0.91

Mounting Pad Layout (Unit: mm)

TO-263



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.