

Features

- Low power loss by high speed switching and low on-resistance
- Excellent thermal behavior
- HBM: JESD22-A114-B: 1B
- Product validation acc. JEDEC Standard



HF

APPLICATIONS

- PFC power supply stages
- Solar inverter
- Telecom
- Server
- UPS

Mechanical Data

- Case: TO-247
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



TO-247

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
SJ65R190U	TO-247	30 pcs / Tube	SJ65R190U

Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V _{DSS}	650	V
Gate-to-Source Voltage	V _{GSS}	±30	V
Continuous Drain Current (T _C = 25°C)	I _D	21	A
Continuous Drain Current (T _C = 100°C)		13.2	A
Pulsed Drain Current (t _p = 10μs, T _C = 25°C)	I _{DM}	84	A
Single Pulse Avalanche Energy *2	E _{AS}	500	mJ
Power Dissipation (T _C = 25°C)	P _D	208	W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Case	R _{θJC}	-	0.41	0.6	°C/W
Thermal Resistance Junction-to-Air	R _{θJA}	-	-	40	°C/W

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	650	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 650V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±30V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *1	V _{GS} = 10V, I _D = 10A	-	0.15	0.19	Ω
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	2	3	4	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	4.4	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = 40V f = 250kHz	-	1579	-	pF
C _{OSS}	Output Capacitance		-	111	-	
C _{RSS}	Reverse Transfer Capacitance		-	4	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time *3	V _{DD} = 400V V _{GS} = 10V I _D = 7A	-	64	-	ns
t _r	Turn-on Rise Time *3		-	16	-	
t _{d(OFF)}	Turn-Off Delay Time *3		-	55	-	
t _f	Turn-Off Fall Time *3		-	14	-	
Q _G	Total Gate-Charge	V _{DD} = 520V V _{GS} = 10V I _D = 10A	-	39	-	nC
Q _{GS}	Gate to Source Charge		-	5	-	
Q _{GD}	Gate to Drain (Miller) Charge		-	14	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *1	I _{SD} = 10A, V _{GS} = 0V	-	0.84	1.2	V
t _{rr}	Reverse Recovery Time	I _F = 1A, V _R = 400V di/dt = 100A/μs	-	138	-	ns
Q _{rr}	Reverse Recovery Charge		-	0.79	-	μC

Notes:

- The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
- The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 100V, V_{GS} = 15V, L = 50mH$
- Guaranteed by design, not subject to production

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current
and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature




Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature




Fig 13 Safe Operation Area





Fig 14 Maximum transient thermal impedance

Package Outline Dimensions (Unit: mm)



TO-247		
Dimension	Min.	Max.
A	15.50	16.10
B	20.70	21.30
C	4.70	5.30
D	1.80	2.20
E	5.20	5.80
F	19.70	20.30
G	5.20	5.60
H	3.30	3.70
I	3.90	4.30
J	0.50	0.70
K	2.80	3.20
L	1.00	1.40
M	2.20	2.60
N	7.00	7.20
O	4.90	5.30
P	1.80	2.20
Q	5.70	5.90
R	0.80	1.20
S	17.00	17.80
T	13.60	14.20

IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.