



Features

- Excellent h_{FE} linearity
- RoHS compliant with Halogen-free
- Qualified to AEC-Q101 Standards

HF

Mechanical Data

- Case: SOT-323
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-323

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
T2SA1579-P	SOT-323	3000 pcs / Tape & Reel	RP
T2SA1579-R	SOT-323	3000 pcs / Tape & Reel	RR
T2SA1579-S	SOT-323	3000 pcs / Tape & Reel	RS

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	-120	V
Collector-Emitter Breakdown Voltage	V_{CEO}	-120	V
Emitter-Base Breakdown Voltage	V_{EBO}	-5	V
Collector Current (Continuous)	I_C	-50	mA
Collector Current (Peak)	I_{CM}	-100	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	0.2	W
Thermal Resistance Junction-to-Air	$R_{\theta JA}$	625	$^\circ\text{C/W}$
Junction Temperature Range	T_J	-55 ~ +150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = -50\mu\text{A}, I_E = 0$	-120	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -1\text{mA}, I_B = 0$	-120	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = -50\mu\text{A}, I_C = 0$	-5	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = -100\text{V}, I_E = 0$	-	-	-0.5	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB} = -4\text{V}, I_C = 0$	-	-	-0.5	μA
DC Current Gain	h_{FE}	$V_{CE} = -6\text{V}, I_C = -2\text{mA}$	180	-	560	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -10\text{mA}, I_B = -1\text{mA}$	-	-	-0.5	V
Base-emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = -10\text{mA}, I_B = -1\text{mA}$	-	-	-1	V
Collector-base Output Capacitance	C_{OBO}	$V_{CB} = -12\text{V}, f = 1\text{MHz}, I_E = 0$	-	3.2	-	pF
Current-Gain— Bandwidth Product	f_T	$I_C = -2\text{mA}, V_{CE} = -12\text{V}$ $f = 30\text{MHz}$	-	140	-	MHz

Classification of h_{FE}

Rank	P	R	S
Range	120-270	180-390	270-560
Marking	RP	RR	RS

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C





Fig 4 $V_{BE(on)}$ vs. I_C

Package Outline Dimensions (Unit: mm)



SOT-323		
Dimension	Min.	Max.
A	2.00	2.20
B	1.15	1.35
C	0.90	1.10
D	0.15	0.35
E	0.25	0.40
G	1.20	1.40
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40

Mounting Pad Layout (Unit: mm)

SOT-323

