


Transient Voltage Suppressor T6.0SMAJ5.0CA - T6.0SMAJ120CA

Features

- ESD / transient protection of high speed data lines
 - IEC 61000-4-2 (ESD): $\pm 30\text{kV}$ (air), $\pm 30\text{kV}$ (contact)
- Low profile package with built-in strain relief for SMT applications
- Low incremental surge resistance, excellent clamping capability
- 600W peak pulse power capability with very fast response time
- High temperature soldering guaranteed: 260°C / 10s at terminals
- Bi-directional applications
- RoHS compliant with Halogen-free
- Qualified to AEC-Q101 Standards



Mechanical Data

- Case: SMA molded plastic
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Solder plated; solderable per MIL- STD-202, Method 208

Maximum Ratings (@ $T_A = 25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak power dissipation with a 10/1000 μs waveform *1 (FIG.1)	P_{PPM}	600	W
Peak pulse current with a 10/1000 μs waveform *1	I_{PP}	see E. Characteristics	A
Typical Thermal Resistance *2	$R_{\theta JA}$	70	$^{\circ}\text{C/W}$
	$R_{\theta JC}$	25	
	$R_{\theta JL}$	30	
Operating junction and storage temperature range	T_J, T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$

Note *1: Non-repetitive current pulses, per Fig. 3 and derated above $T_A = 25^{\circ}\text{C}$

Note *2: Device mounted on p.c.b. with 10 mm x 20 mm x 0.1 mm copper pad area

Transient Voltage Suppressor T6.0SMAJ5.0CA - T6.0SMAJ120CA

Electrical Characteristics (@T_A = 25°C unless otherwise specified)

Type	Marking code	Breakdown Voltage V _{BR} @I _T		Test Current	Reverse Stand off Voltage	Max. Reverse Leakage@ V _{RWM}	Max. Peak Pulse Current	Max. Clamping Voltage @I _{PP}
		V		I _T	V _{RWM}	I _R	I _{PP}	V _C
		Min	Max	mA	V	uA	A	V
T6.0SMAJ5.0CA	IZ	6.4	7.07	10	5	800	65.2	9.2
T6.0SMAJ6.8CA	AG	7.56	8.35	10	6.8	200	54.6	11
T6.0SMAJ7.0CA	AM	7.78	8.6	10	7	200	50	12
T6.0SMAJ7.5CA	AR	8.33	9.21	1	7.5	100	46.5	12.9
T6.0SMAJ8.0CA	AV	8.89	9.83	1	8	50	44.1	13.6
T6.0SMAJ9.0CA	AZ	10	11.1	1	9	10	39	15.4
T6.0SMAJ10CA	BG	11.1	12.3	1	10	5	35.3	17
T6.0SMAJ11CA	BM	12.2	13.5	1	11	1	33	18.2
T6.0SMAJ12CA	BR	13.3	14.7	1	12	1	30.2	19.9
T6.0SMAJ13CA	BV	14.4	15.9	1	13	1	27.9	21.5
T6.0SMAJ14CA	BZ	15.6	17.2	1	14	1	25.9	23.2
T6.0SMAJ15CA	CG	16.7	18.5	1	15	1	24.6	24.4
T6.0SMAJ16CA	CM	17.8	19.7	1	16	1	23.1	26
T6.0SMAJ17CA	CR	18.9	20.9	1	17	1	21.7	27.6
T6.0SMAJ18CA	CV	20	22.1	1	18	1	20.5	29.2
T6.0SMAJ20CA	CZ	22.2	24.5	1	20	1	18.5	32.4
T6.0SMAJ22CA	DG	24.4	26.9	1	22	1	16.9	35.5
T6.0SMAJ24CA	DM	26.7	29.5	1	24	1	15.4	38.9
T6.0SMAJ26CA	DR	28.9	31.9	1	26	1	14.3	42.1
T6.0SMAJ28CA	DV	31.1	34.4	1	28	1	13.2	45.4
T6.0SMAJ30CA	DZ	33.3	36.8	1	30	1	12.4	48.4
T6.0SMAJ33CA	EG	36.7	40.6	1	33	1	11.3	53.3
T6.0SMAJ36CA	EM	40	44.2	1	36	1	10.3	58.1
T6.0SMAJ40CA	ER	44.4	49.1	1	40	1	9.3	64.5
T6.0SMAJ43CA	EV	47.8	52.8	1	43	1	8.6	69.4
T6.0SMAJ45CA	EZ	50	55.3	1	45	1	8.3	72.7
T6.0SMAJ48CA	FG	53.3	58.9	1	48	1	7.8	77.4
T6.0SMAJ51CA	FM	56.7	62.7	1	51	1	7.3	82.4

Transient Voltage Suppressor T6.0SMAJ5.0CA - T6.0SMAJ120CA

Type	Marking code	Breakdown Voltage $V_{BR}@I_T$		Test Current	Reverse Stand off Voltage	Max. Reverse Leakage@ V_{RWM}	Max. Peak Pulse Current	Max. Clamping Voltage @ I_{PP}
		V		I_T	V_{RWM}	I_R	I_{PP}	V_C
		Min	Max	mA	V	uA	A	V
T6.0SMAJ54CA	FR	60	66.3	1	54	1	6.9	87.1
T6.0SMAJ58CA	FV	64.4	71.2	1	58	1	6.4	93.6
T6.0SMAJ60CA	FZ	66.7	73.7	1	60	1	6.2	96.8
T6.0SMAJ64CA	GG	71.1	78.6	1	64	1	5.8	103
T6.0SMAJ68CA	GM	75.5	83.5	1	68	1	5.5	109
T6.0SMAJ70CA	GR	77.8	86	1	70	1	5.3	113
T6.0SMAJ75CA	GV	83.3	92.1	1	75	1	5	121
T6.0SMAJ78CA	GZ	86.7	95.8	1	78	1	4.8	126
T6.0SMAJ85CA	HG	94.4	104	1	85	1	4.4	137
T6.0SMAJ90CA	HM	100	111	1	90	1	4.1	146
T6.0SMAJ100CA	HR	111	123	1	100	1	3.7	162
T6.0SMAJ110CA	HV	122	135	1	110	1	3.4	177
T6.0SMAJ120CA	HZ	133	147	1	120	1	3.1	193

Transient Voltage Suppressor T6.0SMAJ5.0CA - T6.0SMAJ120CA

Ratings and Characteristic Curves (@T_A=25°C unless otherwise noted)

Fig.1 Peak Pulse Power Rating Curve




Fig.2 DERATING CURVE






Fig.3 Pulse Waveform




Transient Voltage Suppressor T6.0SMAJ5.0CA - T6.0SMAJ120CA

Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)



Ordering Information

Part Number	Package	Shipping Quantity
T6.0SMAJ5.0CA - T6.0SMAJ120CA	SMA	5000 pcs / Tape & Reel