



Features

- Fast switching speed
- High conductance
- RoHS compliant with Halogen-free
- Qualified to AEC-Q101 Standards

HF



SOT-353

Mechanical Data

- Case: SOT-353
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TBAS21K	SOT-353	3000 pcs / Tape & Reel	KJS

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Repetitive Peak Reverse Voltage	V _{RRM}	250	V
Working Peak Reverse Voltage	V _{RWM}	200	V
DC Blocking Voltage	V _R	200	V
RMS Reverse Voltage	V _{R(RMS)}	141	V
Forward Continuous Current	I _F	200	mA
Non-Repetitive Peak Forward Surge Current, t = 8.3ms	I _{FSM}	2	A
Non-Repetitive Peak Forward Surge Current, t = 1ms	I _{FSM}	2.5	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation *1	P _D	385	mW
Thermal Resistance Junction-to-Air *1	R _{θJA}	325	°C/W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Note 1: FR-5 = 1.0 * 0.75 * 0.062 in.

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 100\mu\text{A}$	250	-	-	V
Forward Voltage	V_F	$I_F = 100\text{mA}$	-	-	1.00	V
		$I_F = 200\text{mA}$	-	-	1.25	V
Maximum Peak Reverse Current	I_R	$V_R = 200\text{V}, T_J = 25^\circ\text{C}$	-	-	100	nA
		$V_R = 200\text{V}, T_J = 150^\circ\text{C}$	-	-	100	μA
Total Capacitance	C_J	$V_R = 0\text{V}, f = 1.0\text{MHz}$	-	-	5	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 10\text{mA}$ $I_{rr} = 0.1 \times I_R, R_L = 100\Omega$	-	-	50	ns

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Typical Reverse Characteristic




Fig 2 Typical Forward Characteristics





Fig 3 Capacitance vs. Reverse Voltage

Package Outline Dimensions (Unit: mm)



SOT-353		
Dimension	Min.	Max.
A	2.00	2.20
B	1.15	1.35
C	0.85	1.05
D	0.15	0.35
E	0.25	0.40
F	1.20	1.40
G	0.60	0.70
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40

Package Outline Dimensions (Unit: mm)

SOT-353

