


Features

- Fast switching speed
- High conductance
- RoHS compliant with Halogen-free
- Qualified to AEC-Q101 Standards

HF

Mechanical Data

- Case: SOT-23-6L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



SOT-23-6L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TBAS21RT-6L	SOT-23-6L	3000 pcs / Tape & Reel	B5R

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Repetitive Peak Reverse Voltage	V _{RRM}	250	V
DC Blocking Voltage	V _R	200	V
Average Rectified Output Current	I _F	200	mA
Non-repetitive Peak Forward Surge Current, t _p = 10ms	I _{FSM}	2	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	300	mW
Thermal Resistance Junction-to-Air	R _{θJA}	417	°C/W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 100\mu\text{A}$	200	-	-	V
Forward Voltage	V_F	$I_F = 100\text{mA}$	-	-	1	V
		$I_F = 200\text{mA}$	-	-	1.25	V
Maximum Peak Reverse Current	I_R	$V_R = 200\text{V}, T_J = 25^\circ\text{C}$	-	-	0.1	μA
		$V_R = 200\text{V}, T_J = 150^\circ\text{C}$	-	-	100	μA
Total Capacitance	C_J	$V_R = 0\text{V}, f = 1.0\text{MHz}$	-	-	5	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 30\text{mA}$ $I_{rr} = 0.1 \times I_R, R_L = 100\Omega$	-	-	50	ns

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Typical Reverse Characteristic




Fig 2 Typical Forward Characteristics




Fig 3 Capacitance vs. Reverse Voltage





Fig 4 Power Derating Curve

Package Outline Dimensions (Unit: mm)



SOT-23-6L		
Dimension	Min.	Max.
A	2.80	3.00
B	1.50	1.70
C	1.00	1.20
D	0.35	0.45
E	0.35	0.55
G	0.90	1.00
H	0.02	0.10
J	0.10	0.20
K	2.60	3.00

Mounting Pad Layout (Unit: mm)

SOT-23-6L

