



Features

- Fast switching speed
- High conductance
- Very low leakage current
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

HF



SOT-23

Mechanical Data

- Case: SOT -23
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TBAW156	SOT-23	3000 pcs / Tape & Reel	K53

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Non-repetitive Peak Reverse Voltage	V _{RM}	60	V
Peak Repetitive Peak Reverse Voltage	V _{RRM}	85	V
Working Peak Reverse Voltage	V _{RWM}	85	V
DC Blocking Voltage	V _R	85	V
Continuous Forward Current (Single diode loaded)	I _F	160	mA
Continuous Forward Current (Double diode loaded)	I _F	140	mA
Repetitive Peak Forward Current	I _{FRM}	500	mA
Peak Forward Surge Current, 1μs Single Half-sine-wave	I _{FSM}	4	A
Peak Forward Surge Current, 1ms Single Half-sine-wave	I _{FSM}	1	A
Peak Forward Surge Current, 1s Single Half-sine-wave	I _{FSM}	0.5	A


Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	250	mW
Thermal Resistance Junction-to-Air	R _{θJA}	500	°C/W
Operating Junction Temperature Range	T _J	-65 ~ +150	°C
Storage Temperature Range	T _{STG}	-65 ~ +150	°C


Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 100\mu\text{A}$	85	-	-	V
Forward Voltage	V_F	$I_F = 1\text{mA}$	-	-	0.90	V
		$I_F = 10\text{mA}$	-	-	1.00	V
		$I_F = 50\text{mA}$	-	-	1.10	V
		$I_F = 150\text{mA}$	-	-	1.25	V
Maximum Peak Reverse Current	I_R	$V_R = 75\text{V}$	-	-	5	nA
		$V_R = 75\text{V}, T_J = 150^\circ\text{C}$	-	-	80	nA
Total Capacitance	C_J	$V_R = 0\text{V}, f = 1.0\text{MHz}$	-	3	-	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 10\text{mA}$ $I_{rr} = 0.1 \times I_R, R_L = 100\Omega$	-	-	4	μs


Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




T_A , AMBIENT TEMPERATURE ($^\circ\text{C}$)
Fig. 1 Power Derating Curve




T_A , AMBIENT TEMPERATURE ($^\circ\text{C}$)
Fig. 2 Current Derating Curve



V_F , INSTANTANEOUS FORWARD VOLTAGE (V)
Fig. 3 Typical Forward Characteristics




T_A , AMBIENT TEMPERATURE ($^\circ\text{C}$)
Fig. 4 Typical Reverse Characteristics



$V_{F(AVE)}$, AVERAGE FORWARD VOLTAGE (V)
Fig. 5 Typical Forward Voltage vs Ambient Temperature


Package Outline Dimensions (Unit: mm)



SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.