



Features

- Complimentary to TBCW68
- High collector current
- High current gain
- Low collector-emitter saturation voltage
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

HF



SOT-23

Mechanical Data

- Case: SOT-23
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TBCW66F	SOT-23	3000 pcs / Tape & Reel	EF
TBCW66G	SOT-23	3000 pcs / Tape & Reel	EG
TBCW66H	SOT-23	3000 pcs / Tape & Reel	EH

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Breakdown Voltage	V _{CBO}	75	V
Collector-Emitter Breakdown Voltage	V _{CEO}	45	V
Emitter-Base Breakdown Voltage	V _{EBO}	5	V
Continuous Collector Current	I _C	0.8	A
Peak Collector Current	I _{CM}	1	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	330	mW
Thermal Resistance Junction-to-Air ^{*1}	R _{θJA}	395	°C/W
Thermal Resistance Junction-to-Case ^{*1}	R _{θJC}	218	°C/W
Thermal Resistance Junction-to-Lead ^{*1}	R _{θJL}	191	°C/W
Operating junction Temperature	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 15mm * 15mm * 1mm FR4-epoxy P.C.B

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter		Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage		$V_{(BR)CBO}$	$I_C = 10\mu\text{A}, I_E = 0$	75	-	-	V
Collector-Emitter Breakdown Voltage		$V_{(BR)CEO}$	$I_C = 10\text{mA}, I_B = 0$	45	-	-	V
Emitter-Base Breakdown Voltage		$V_{(BR)EBO}$	$I_E = 10\mu\text{A}, I_C = 0$	5	-	-	V
Collector Cut-off Current		I_{CBO}	$V_{CB} = 45\text{V}, I_E = 0$	-	-	20	nA
Emitter Cut-off Current		I_{EBO}	$V_{EB} = 4\text{V}, I_C = 0$	-	-	20	nA
DC Current Gain	TBCW66F	h_{FE}	$V_{CE} = 10\text{V}, I_C = 0.1\text{mA}$	35	-	-	-
	TBCW66G			50	-	-	-
	TBCW66H			80	-	-	-
	TBCW66F		$V_{CE} = 1\text{V}, I_C = 10\text{mA}$	75	-	-	-
	TBCW66G			110	-	-	-
	TBCW66H			180	-	-	-
	TBCW66F		$V_{CE} = 1\text{V}, I_C = 100\text{mA}$	100	-	250	-
	TBCW66G			160	-	400	-
	TBCW66H			250	-	630	-
Collector-emitter Saturation Voltage		$V_{CE(sat)}$	$I_C = 100\text{mA}, I_B = 10\text{mA}$	-	-	0.3	V
			$I_C = 500\text{mA}, I_B = 50\text{mA}$	-	-	0.7	V
Base-emitter Saturation Voltage		$V_{BE(sat)}$	$I_C = 100\text{mA}, I_B = 10\text{mA}$	-	-	1.25	V
			$I_C = 500\text{mA}, I_B = 50\text{mA}$	-	-	2	V
Transition Frequency		f_T	$I_C = 50\text{mA}, V_{CE} = 5\text{V}$ $f = 20\text{MHz}$	170	-	-	MHz

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C (TBCW66F)




Fig 2 h_{FE} vs. I_C (TBCW66G)




Fig 3 h_{FE} vs. I_C (TBCW66H)




Fig 4 $V_{BE(ON)}$ vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C





Fig 3 $V_{BE(sat)}$ vs. I_C


Package Outline Dimensions (Unit: mm)



SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.9	1.1
D	0.3	0.5
E	0.35	0.48
G	1.80	2.00
H	0.02	0.1
J	0.05	0.15
K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.