


Features

- Advanced trench technology
- Low gate charge
- Low on-resistance
- Fast switching speed
- RoHS compliant with Halogen-free
- Qualified to AEC-Q101 Standards

HF

Mechanical Data

- Case: DFN2020-6L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



DFN2020-6L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TBL120N03DF1	DFN2020-6L	3000 pcs / Tape & Reel	120N03

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V _{DSS}	30	V
Gate-to-Source Voltage	V _{GSS}	±20	V
Continuous Drain Current (T _C = 25°C)	I _D	30	A
Continuous Drain Current (T _A = 25°C) *1		10	A
Continuous Drain Current (T _A = 100°C) *1		6.4	A
Pulsed Drain Current (t _p = 10μs, T _A = 25°C)	I _{DM}	60	A
Single Pulse Avalanche Energy *3	E _{AS}	18	mJ
Power Dissipation (T _C = 25°C)	P _D	18	W
Power Dissipation (T _A = 25°C) *1		2.4	W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Case	R _{θJC}	-	-	7	°C/W
Thermal Resistance Junction-to-Air *1	R _{θJA}	-	-	52	°C/W

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	30	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 30V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance ^{*2}	V _{GS} = 10V,I _D = 8A	-	10	12	mΩ
		V _{GS} = 4.5V,I _D = 6A	-	15	18	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	1	1.5	2	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	4	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V	-	710	-	pF
C _{OSS}	Output Capacitance	V _{DS} = 15V	-	106	-	
C _{RSS}	Reverse Transfer Capacitance	f = 1.0MHz	-	83	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time ^{*4}	V _{DD} = 15V	-	3	-	ns
t _r	Turn-on Rise Time ^{*4}	V _{GS} = 10V	-	2	-	
t _{d(OFF)}	Turn-Off Delay Time ^{*4}	I _D = 20A	-	13	-	
t _f	Turn-Off Fall Time ^{*4}	R _G = 3Ω	-	6	-	
Q _G	Total Gate-Charge	V _{DD} = 15V	-	13.5	-	nC
Q _{GS}	Gate to Source Charge	V _{GS} = 10V	-	2.5	-	
Q _{GD}	Gate to Drain (Miller) Charge	I _D = 20A	-	3.3	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage ^{*2}	I _{SD} = 20A, V _{GS} = 0V	-	0.9	1.2	V
t _{rr}	Reverse Recovery Time	I _{SD} = 8A, V _{GS} = 0V	-	110	-	ns
Q _{rr}	Reverse Recovery Charge	di/dt = 100A/μs	-	53	-	nC

Notes:

- The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper
- The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
- The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 15V, V_{GS} = 10V, L = 0.1mH$
- Guaranteed by design, not subject to production

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current
and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature





Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature

Package Outline Dimensions (Unit: mm)



DFN2020-6L		
Dimension	Min.	Max.
A	1.924	2.076
B	1.924	2.076
C	0.500	0.600
D	0.250	0.350
E	0.900	1.100
F	0.850	1.050
G	0.200	0.400
H	0.000	0.050
I	0.550	0.750
J	0.103	0.303
K	0.150	0.350
L	0.200	0.400
M	0.700	0.900

Mounting Pad Layout (Unit: mm)

DFN2020-6L

