



## Features

- Tight voltage tolerance:  $\pm 2\%$
- Ultra low-profile package well suited for automated assembly
- Moisture sensitivity level 1
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

HF



SOD-323

## Mechanical Data

- Case: SOD-323
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

## Ordering Information

| Part Number | Package | Shipping Quantity      | Marking Code |
|-------------|---------|------------------------|--------------|
| TBZT52B24S  | SOD-323 | 3000 pcs / Tape & Reel | RZ           |

## Thermal Characteristics


| Parameter                                         | Symbol          | Value      | Unit                 |
|---------------------------------------------------|-----------------|------------|----------------------|
| Power Dissipation                                 | $P_D$           | 200        | mW                   |
| Thermal Resistance Junction-to-Air <sup>*1</sup>  | $R_{\theta JA}$ | 426        | $^{\circ}\text{C/W}$ |
| Thermal Resistance Junction-to-Case <sup>*1</sup> | $R_{\theta JC}$ | 230        | $^{\circ}\text{C/W}$ |
| Thermal Resistance Junction-to-Lead <sup>*1</sup> | $R_{\theta JL}$ | 297        | $^{\circ}\text{C/W}$ |
| Operating Junction Temperature Range              | $T_J$           | -55 ~ +150 | $^{\circ}\text{C}$   |
| Storage Temperature Range                         | $T_{STG}$       | -65 ~ +150 | $^{\circ}\text{C}$   |

Note 1: The data tested by surface mounted on a 15mm \* 15mm \* 1mm FR4-epoxy P.C.B


## Electrical Characteristics (@ $T_A = 25^{\circ}\text{C}$ unless otherwise specified)

| Parameter               | Symbol   | Test Condition        | Min.  | Typ. | Max.  | Unit                         |
|-------------------------|----------|-----------------------|-------|------|-------|------------------------------|
| Zener Voltage           | $V_Z$    | $I_{ZT} = 5\text{mA}$ | 23.52 | 24   | 24.48 | V                            |
| Forward Voltage         | $V_F$    | $I_F = 10\text{mA}$   | -     | -    | 0.9   | V                            |
| Maximum Reverse Current | $I_R$    | $V_R = 16.8\text{V}$  | -     | -    | 0.045 | $\mu\text{A}$                |
| Maximum Zener Impedance | $Z_{ZT}$ | $I_{ZT} = 5\text{mA}$ | -     | -    | 65    | $\Omega$                     |
| Maximum Zener Impedance | $Z_{ZK}$ | $I_{ZK} = 1\text{mA}$ | -     | -    | 235   | $\Omega$                     |
| Temperature Coefficient | $T_C$    | $I_{ZT} = 5\text{mA}$ | 18.4  | 19.7 | 22    | $\text{mV}/^{\circ}\text{C}$ |


**TYPICAL CHARACTERISTICS** (@  $T_A = 25^\circ\text{C}$  unless otherwise specified)




**Fig 1 Steady State Power Derating**




**Fig 2 Typical Zener Breakdown Characteristics**



**Fig 3 Zener Impedance vs. Zener Current**




**Fig 4 Typical Forward Characteristics**



**Fig 5 Typical Reverse Characteristics**


## Package Outline Dimensions (Unit: mm)



| SOD-323   |      |      |
|-----------|------|------|
| Dimension | Min. | Max. |
| A         | 1.60 | 1.80 |
| B         | 1.20 | 1.40 |
| C         | 0.80 | 0.90 |
| D         | 0.25 | 0.35 |
| E         | 0.22 | 0.42 |
| H         | 0.02 | 0.10 |
| J         | 0.05 | 0.15 |
| K         | 2.55 | 2.75 |

## Mounting Pad Layout (Unit: mm)

### SOD-323



## Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.