Dual Digital Transistors


TEMH11


Features

- Two DTC114E transistors are built-in a package
- Epitaxial planar die construction
- Built-in biasing resistors (R_1: 10kΩ, R_2: 10kΩ)
- Also available in lead free version
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

Mechanical Data

- Case: SOT-563
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208





SOT-563

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TEMH11	SOT-563	3000 pcs / Tape & Reel	H11

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value		Unit
		TR1	TR2	
Supply Voltage	V_{CC}	50	50	V
Input Voltage	V_{IN}	-10 to +40	-10 to +40	V
Output Current	I_O	50	50	mA
Collector Current	$I_{C(Max)}$	100	100	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	150	mW
Operating Junction Temperature Range	T_J	-55 ~ +150	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

Electrical Characteristics-TR1 and TR2 (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Input Voltage	$V_{I(off)}$	V_{CC} = 5V, I_O = 100μA	0.5	-	-	V
	$V_{I(on)}$	V_O = 0.3V, I_O = 10mA	-	-	3	V
Output Voltage	$V_{O(on)}$	Io = 10mA, I_I = 0.5mA	-	0.1	0.3	V
Input Current	I_I	V_I = 5V	-	-	0.88	mA
Output Current	$I_{O(off)}$	V_{CC} = 50V, V_I = 0V	-	-	0.5	μA
DC Current Gain	G_I	V_O = 5V, I_O = 5mA	30	-	-	-
Input Resistor	R_1		7	10	13	kΩ
Resistance Ratio	R2/R1		0.8	1	1.2	
Gain-Bandwidth Product	f_T	V_{CE} = 10V, I_E = 5mA, f = 100MHz	-	250	-	MHz

Ratings and Characteristics Curves-TR1 and TR2 (@ T_A = 25°C unless otherwise specified)




Fig 1 Input Voltage vs Output Current




Fig 2 Output Current vs Input Voltage




Fig 3 DC Current Gain vs Output Current





Fig 4 Output Voltage vs Output Current


Package Outline Dimensions (Unit: mm)



SOT-563		
Dimension	**Min.**	**Max.**
A	1.500	1.700
B	1.100	1.300
C	0.525	0.600
D	0.170	0.270
E	0.100	0.300
G	0.450	0.550
H	0.000	0.050
J	0.090	0.160
K	1.500	1.700

Package Outline Dimensions (Unit: mm)

SOT-563



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.