


Super-Fast Recovery Rectifier

TES2H - TES2J

Features

- Low forward voltage drop
- High forward surge current capability
- Low-profile SMD ideal for automated manufacturing
- RoHS compliant with Halogen-free
- Qualified to AEC-Q101 Standards



Mechanical Data

- Case: SMB molded plastic
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Solder plated; solderable per MIL- STD-202, Method 208
- Polarity: Color band denotes cathode end

Maximum Ratings (@T_A = 25°C unless otherwise specified)

Parameter	Symbol	TES2H	TES2J	Unit
Peak Repetitive Reverse Voltage	V _{RRM}	500	600	V
RMS Reverse Voltage	V _{RMS}	350	420	V
DC Blocking Voltage	V _{DC}	500	600	V
Maximum Average Forward Output Current	I _{F(AV)}	2.0		A
Peak Forward Surge Current, 8.3ms Single Half Sine wave	I _{FSM}	50		A

Thermal Characteristics

Parameter	Symbol	TES2H	TES2J	Unit
Typical Thermal Resistance *1	R _{θJA}	60		°C/W
	R _{θJC}	23		
	R _{θJL}	25		
Operating Junction Temperature Range	T _J	-55 ~ +150		°C
Storage Temperature Range	T _{STG}	-55 ~ +150		°C

Note *1: Device mounted on p.c.b. with 10 mm x 20 mm x 0.1mm copper pad area

Super-Fast Recovery Rectifier

TES2H - TES2J

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition		Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R = 2\mu\text{A}$, TES2H		500	-	-	V
		$I_R = 2\mu\text{A}$, TES2J		600	-	-	V
Instantaneous Forward Voltage	V_F	$I_F = 2.0\text{A}$		-	-	1.7	V
Reverse Current	I_R	Rated	@ $T_A = 25^\circ\text{C}$	-	-	5.0	μA
		V_R	@ $T_A = 125^\circ\text{C}$	-	-	200.0	
Reverse Recovery Time	t_{rr}	$I_F = 0.5\text{A}$, $I_{rr} = 0.25\text{A}$, $I_R = 1\text{A}$		-	-	35	ns

Super-Fast Recovery Rectifier

TES2H - TES2J

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Surge Current Derating Curve




Fig.3 Typical Forward Voltage Characteristics






Fig.4 Typical Reverse Characteristics




Super-Fast Recovery Rectifier

TES2H - TES2J

Package Outline Dimensions (unit: mm)



Mounting Pad Layout (unit: mm)



Ordering Information

Part Number	Marking	Package	Shipping Quantity
TES2H	ES2H	SMB	3000 pcs / Tape & Reel
TES2J	ES2J	SMB	3000 pcs / Tape & Reel