银河微电 Galaxy Microelectronics


PNP Silicon Epitaxial Planar Transistor


TFMMT593

Features

HF

- High saturation voltage
- Complementary to TFMMT493
- Excellent h_{FE} linearity
- Halogen free
- Qualified to AEC-Q101 standards for high reliability





SOT-23

Mechanic al Data

- Case: SOT-23
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TFMMT593	SOT-23	3000 pcs / Tape & Reel	593

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Breakdown Voltage	V_{CBO}	-120	V
Collector-Emitter Breakdown Voltage	V_{CEO}	-100	V
Emitter-Base Breakdown Voltage	V_{EBO}	-5	V
Collector Current (continuous)	I_C	-1	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation(T_A = 25°C)	P_D	500	mW
Thermal Resistance Junction-to-Air *1	$R_{\theta JA}$	274	°C/W
Thermal Resistance Junction-to-Case *1	$R_{\theta JC}$	127	°C/W
Thermal Resistance Junction-to-Lead *1	$R_{\theta JL}$	180	°C/W
Junction Temperature Range	T_J	-55 ~ +150	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 15mm * 15mm * 2mm FR4-epoxy P.C.B

Electrical Characteristics (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	I_C = -100μA, I_E = 0	-120	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	I_C = -10mA, I_B = 0	-100	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	I_E = -100μA, I_C = 0	-5	-	-	V
Collector Cut-off Current	I_{CBO}	V_{CB} = -100V, I_E = 0	-	-	-0.1	μA
Emitter Cut-off Current	I_{EBO}	V_{EB} = -4V, I_C = 0	-	-	-0.1	μA
DC Current Gain	h_{FE}	V_{CE} = -5V, I_C = -1mA	100	-	-	-
		V_{CE} = -5V, I_C = -250mA	100	-	-	-
		V_{CE} = -5V, I_C = -500mA	100	-	300	-
		V_{CE} = -5V, I_C = -1A	50	-	-	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	I_C = -250mA, I_B = -25mA	-	-	-0.2	V
		I_C = -500mA, I_B = -50mA	-	-	-0.3	V
Base-emitter Saturation Voltage	$V_{BE(sat)}$	I_C = -500mA, I_B = -50mA	-	-	-1.1	V
Base-emitter Voltage	$V_{BE(on)}$	V_{CE} = -5V, I_C = -1A	-	-	-1.0	V
Transition Frequency	f_T	I_C = -50mA, V_{CE} = -10V f = 100MHz	50	-	-	MHz
Output Capacitance	C_{ob}	V_{CB} = -10V , I_E = 0A , f = 1MHz	-	-	5	pF

Ratings and Characteristics Curves (@ T_A = 25°C unless otherwise specified)




Fig. 1 Collector-Emitter Saturation Voltage vs. Collector Current




Fig. 2 Base-emitter Saturation Voltage vs. Collector Current




Fig. 3 DC Current Gain vs. Collector Current




Fig. 4 Collector-Emitter Saturation Voltage vs. Collector Current




Fig. 5 Base-emitter Voltage vs. Collector Current





Fig 6 Output Characteristics


Package Outline Dimensions (Unit: mm)



SOT-23		
Dimension	**Min.**	**Max.**
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.