



Features

- ESD / transient protection of high speed data lines
 - IEC 61000-4-2 (ESD): ± 30 kV (air), ± 30 kV (contact)
- Working voltage: $V_{RWM} = 6.2V$
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

HF



SOD-323

Mechanical Data

- Case: SOD-323
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TGESD6V2D3	SOD-323	3000 pcs / Tape & Reel	3D

Maximum Ratings (@ $T_A = 25^\circ C$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power ($t_p = 8 / 20\mu s$)	P_{PP}	150	W
Reverse Working Voltage	V_{RWM}	6.2	V
ESD According to IEC61000-4-2 Air	V_{ESD}	± 30	kV
ESD According to IEC61000-4-2 Contact Discharge	V_{ESD}	± 30	kV

Thermal Characteristics

Parameter	Symbol	Value	Unit
Operating Junction Temperature Range	T_J	$-55 \sim +150$	$^\circ C$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ C$

Electrical Characteristics (@ $T_A = 25^\circ C$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
V_{BR}	Reverse Breakdown Voltage	$I_T = 1mA$	6.2	-	7.8	V
I_R	Reverse Leakage Current	$V_{RWM} = 6.2V$	-	-	1000	nA
V_C	Clamping Voltage	$I_{PP} = 1A, t_p = 8/20\mu s$	-	-	8.5	V
		$I_{PP} = 10A, t_p = 8/20\mu s$	-	-	15	V
C_J	Junction Capacitance	$V_R = 0V, f = 1.0MHz$	-	-	120	pF

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 8/20 μs waveform per IEC61000-4-5




Fig 2 ESD pulse waveform according to IEC61000-4-2





Fig 3 Power Derating Curve


Package Outline Dimensions (Unit: mm)



SOD-323		
Dimension	Min.	Max.
A	1.60	1.80
B	1.20	1.40
C	0.80	0.90
D	0.25	0.35
E	0.22	0.42
H	0.02	0.10
J	0.05	0.15
K	2.55	2.75

Mounting Pad Layout (Unit: mm)

SOD-323



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.