

Switching Diode
TMMBD4148

Features

- Fast switching speed
- High conductance
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

HF





SOT-23

Mechanical Data

- Case: SOT-23
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TMMBD4148	SOT-23	3000 pcs / Tape & Reel	KA2

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Non-Repetitive Peak Reverse Voltage	V_{RM}	100	V
Peak Repetitive Peak Reverse Voltage	V_{RRM}	75	V
Working Peak Reverse Voltage	V_{RWM}	75	V
DC Blocking Voltage	V_R	75	V
RMS Reverse Voltage	$V_{R(RMS)}$	53	V
Average Rectified Output Current	I_o	150	mA
Peak Forward Surge Current, 1μs Single Half-sine-wave	I_{FSM}	2	A
Peak Forward Surge Current, 1s Single Half-sine-wave	I_{FSM}	1	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	350	mW
Thermal Resistance Junction-to-Air	$R_{\theta JA}$	357	°C/W
Operating Junction Temperature Range	T_J	-65 ~ +150	°C
Storage Temperature Range	T_{STG}	-65 ~ +150	°C

Electrical Characteristics (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	I_R = 100μA	75	-	-	V
Forward Voltage	V_F	I_F = 1mA	-	-	0.715	V
		I_F = 10mA	-	-	0.855	V
		I_F = 50mA	-	-	1.000	V
		I_F = 150mA	-	-	1.250	V
Maximum Peak Reverse Current	I_R	V_R = 20V	-	-	25	nA
		V_R = 75V	-	-	2.5	μA
Total Capacitance	C_J	V_R = 0V, f = 1.0MHz	-	-	2	pF
Reverse Recovery Time	t_{rr}	I_F = I_R = 10mA I_{rr} = 0.1×I_R, R_L = 100Ω	-	-	4	ns

Ratings and Characteristics Curves (@ T_A = 25°C unless otherwise specified)




Fig 1 Typical Reverse Characteristic




Fig 2 Typical Forward Characteristics




Fig 3 Capacitance vs. Reverse Voltage





Fig 4 Power Derating Curve


Package Outline Dimensions (Unit: mm)



SOT-23		
Dimension	**Min.**	**Max.**
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.