

PNP High Voltage Amplifier

TMMBTA94


FEATURES

- Low collector-emitter saturation voltage
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

HF

APPLICATIONS

- High voltage switch
- Telephone switch



ORDERING INFORMATION

Type No.	Marking	Package Code
TMMBTA94	4D	SOT-23

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Symbol	Parameter	Value	UNIT
V _{CBO}	collector-base voltage	-400	V
V _{CEO}	collector-emitter voltage	-400	V
V _{EBO}	emitter-base voltage	-6	V
I _C	collector current (DC)	-0.3	A
P _C	Collector dissipation	0.35	W
T _J , T _{STG}	junction and storage temperature	-40 to +150	°C

PNP High Voltage Amplifier

TMMBTA94





ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified

Symbol	Parameter	Test conditions	MIN.	MAX.	UNIT
$V_{(BR)CBO}$	Collector-base breakdown voltage	$I_C=-100\mu A, I_E=0$	-400		
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C=-1mA, I_B=0$	-400		
$V_{(BR)EBO}$	Emitter-base breakdown voltage	$I_E=-10\mu A, I_C=0$	-6		
I_{CBO}	collector cut-off current	$I_E=0; V_{CB}=-350V$	-	-0.1	μA
I_{CES}	collector cut-off current	$V_{BE}=0; V_{CE}=-350V$	-	-0.5	μA
I_{EBO}	emitter cut-off current	$I_C=0; V_{EB}=-4V$	-	-0.1	μA
h_{FE}	DC current gain	$V_{CE}=-10V; I_C=-1mA$ $V_{CE}=-10V; I_C=-10mA$ $V_{CE}=-10V; I_C=-50mA$ $V_{CE}=-10V; I_C=-100mA$	40 100 45 20	- 200 - -	
$V_{CE(sat)}$	Collector-emitter saturation voltage	$I_C=-1mA, I_B=-0.1mA$ $I_C=-10mA, I_B=-1mA$ $I_C=-50mA, I_B=-5mA$	-	-0.4 -0.5 -0.75	V
$V_{BE(sat)}$	Base-emitter saturation voltage	$I_C=-10mA; I_B=-1mA$	-	-0.75	V
C_{ob}	Collector output capacitance	$V_{CB}=-20V, I_E=0, f=1MHz$		7	pF

PNP High Voltage Amplifier

TMMBTA94

TYPICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified




PNP High Voltage Amplifier

TMMBTA94


PACKAGE OUTLINE

Plastic surface mounted package

SOT-23



SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
TMMBTA94	SOT-23	3000 pcs / Tape & Reel