Dual NPN Silicon Epitaxial Planar Transistor

TMMDT3904


Features


HF

- Epitaxial planar die construction
- Complimentary to TMMDT3906
- Ultra-small surface mount package
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

Mechanical Data

- Case: SOT-363
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208





SOT-363

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TMMDT3904	SOT-363	3000 pcs / Tape & Reel	K6N

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Breakdown Voltage	V_{CBO}	60	V
Collector-Emitter Breakdown Voltage	V_{CEO}	40	V
Emitter-Base Breakdown Voltage	V_{EBO}	6	V
Collector Current (Continuous)	I_C	0.2	A
Collector Current (Peak)	I_{CM}	0.2	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	200	mW
Thermal Resistance Junction-to-Air	$R_{\theta JA}$	625	°C/W
Thermal Resistance Junction-to-Air *1	$R_{\theta JA}$	513	°C/W
Thermal Resistance Junction-to-Case *1	$R_{\theta JC}$	322	°C/W
Thermal Resistance Junction-to-Lead *1	$R_{\theta JL}$	404	°C/W
Ambient Temperature	T_A	-55 ~ +150	°C
Operating junction Temperature	T_J	-55 ~ +150	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a minimum recommended FR-4 board

Electrical Characteristics (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	I_C = 10μA, I_E = 0	60	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	I_C = 100μA, I_B = 0	40	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	I_E = 10μA, I_C = 0	6	-	-	V
Collector Cut-off Current	I_{CEX}	V_{CE} = 30V, $V_{EB(OFF)}$ = 3V	-	-	50	nA
Base Cut-off Current	I_{BL}	V_{CE} = 30V, $V_{EB(OFF)}$ = 3V	-	-	50	nA
DC Current Gain	h_{FE}	V_{CE} = 1V, I_C = 0.1mA	40	-	-	-
		V_{CE} = 1V, I_C = 1mA	70	-	-	-
		V_{CE} = 1V, I_C = 10mA	100	-	300	-
		V_{CE} = 1V, I_C = 50mA	60	-	-	-
		V_{CE} = 1V, I_C = 100mA	30	-	-	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	I_C = 10mA, I_B = 1mA	-	-	0.2	V
		I_C = 50mA, I_B = 5mA	-	-	0.3	V
Base-emitter Saturation Voltage	$V_{BE(sat)}$	I_C = 10mA, I_B = 1mA	0.65	-	0.85	V
		I_C = 50mA, I_B = 5mA	-	-	0.95	V
Transition Frequency	f_T	I_C = 10mA, V_{CE} = 20V	300	-	-	MHz
Collector Output Capacitance	C_{OBO}	V_{CB} = 5V, I_E = 0, f = 1MHZ	-	-	4	pF
Input Capacitance	C_{IBO}	V_{EB} = 0.5V, I_C = 0, f = 1MHz	-	-	8	pF
Noise Figure	N_F	V_{CE} = 5V, I_C = 100μA, R_S = 1kΩ f = 1kHz	-	-	5	dB
Delay Time	t_d	V_{CC} = 3V, I_C = 10mA $V_{BE(OFF)}$ = -0.5V, I_{B1} = 1mA	-	-	35	ns
Rise Time	t_r		-	-	35	ns
Storang Time	t_s	V_{CC} = 3V, I_C = 10mA I_{B1} = I_{B2} = 1mA	-	-	200	ns
Fall Time	t_f		-	-	50	ns

Ratings and Characteristics Curves (@ T_A = 25°C unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C




Fig 4 $V_{BE(ON)}$ vs. I_C




Fig 5 I_C vs. V_{CE}




Fig 6 P_D vs. T_A





Fig 7 C_J vs. V_R


Package Outline Dimensions (Unit: mm)



SOT-363		
Dimension	**Min.**	**Max.**
A	2.00	2.20
B	1.15	1.35
C	0.85	1.05
D	0.15	0.35
E	0.25	0.40
G	0.60	0.70
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40

Mounting Pad Layout (Unit: mm)

SOT-363



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.