



Features

- Epitaxial planar die construction
- Two internal isolated NPN/PNP transistors in one package
- Ultra-small surface mount package
- Halogen free
- Qualified to AEC-Q101 standards for high reliability

HF



SOT-363

Mechanical Data

- Case: SOT-363
- Molding compo und: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
TMMDT3946	SOT-363	3000 pcs / Tape & Reel	K46

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	NPN	PNP	Unit
Collector-Base Voltage	V _{CBO}	60	-40	V
Collector-Emitter Voltage	V _{CEO}	40	-40	V
Emitter-Base Voltage	V _{EBO}	5	-5	V
Collector Current (Continuous)	I _C	200	-200	mA
Collector Current (Peak)	I _{CM}	200	-200	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	200	mW
Thermal Resistance Junction-to-Air *1	R _{θJA}	513	°C/W
Thermal Resistance Junction-to-Case *1	R _{θJC}	322	°C/W
Thermal Resistance Junction-to-Lead *1	R _{θJL}	404	°C/W
Operating Junction Temperature	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 15mm * 15mm * 1mm FR4-epoxy P.C.B

Electrical Characteristics of NPN Transistor (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10\mu\text{A}, I_E = 0$	60	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1\text{mA}, I_B = 0$	40	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10\mu\text{A}, I_C = 0$	5	-	-	V
Collector Cut-off Current	I_{CEX}	$V_{CE} = 30\text{V}, V_{EB(OFF)} = 3\text{V}$	-	-	50	nA
Base Cut-off Current	I_{BL}	$V_{CE} = 30\text{V}, V_{EB(OFF)} = 3\text{V}$	-	-	50	nA
DC Current Gain	h_{FE}	$V_{CE} = 1\text{V}, I_C = 0.1\text{mA}$	40	-	-	-
		$V_{CE} = 1\text{V}, I_C = 1\text{mA}$	70	-	-	-
		$V_{CE} = 1\text{V}, I_C = 10\text{mA}$	100	-	300	-
		$V_{CE} = 1\text{V}, I_C = 50\text{mA}$	60	-	-	-
		$V_{CE} = 1\text{V}, I_C = 100\text{mA}$	30	-	-	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 10\text{mA}, I_B = 1\text{mA}$	-	-	0.2	V
		$I_C = 50\text{mA}, I_B = 5\text{mA}$	-	-	0.3	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 10\text{mA}, I_B = 1\text{mA}$	0.65	-	0.85	V
		$I_C = 50\text{mA}, I_B = 5\text{mA}$	-	-	0.95	V
Transition Frequency	f_T	$V_{CE} = 20\text{V}, I_C = 20\text{mA}$ $f = 100\text{MHz}$	300	-	-	MHz
Output Capacitance	C_{OBO}	$V_{CB} = 5\text{V}, f = 1.0\text{MHz}, I_E = 0$	-	-	4	pF
Input Capacitance	C_{OBI}	$I_C = 0, V_{EB} = 0.5\text{V}; f = 1\text{MHz}$	-	-	8	pF
Noise Figure	N_F	$I_C = 0.1\text{mA}, V_{CE} = 5\text{V}$ $R_S = 1\text{k}\Omega, f = 1\text{kHz}$	-	-	5	dB
Delay Time	t_D	$V_{CC} = 3\text{V}, V_{BE(off)} = -0.5\text{V}$	-	-	35	ns
Rise Time	t_R	$I_C = 10\text{mA}, I_{B1} = I_{B2} = 1\text{mA}$	-	-	35	ns
Storage Time	t_S	$V_{CC} = 3\text{V}, I_C = 10\text{mA}$	-	-	200	ns
Fall Time	t_F	$I_{B1} = I_{B2} = 1\text{mA}$	-	-	50	ns

Electrical Characteristics of PNP Transistor (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = -10\mu\text{A}$, $I_E = 0$	-40	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -1\text{mA}$, $I_B = 0$	-40	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = -10\mu\text{A}$, $I_C = 0$	-5	-	-	V
Collector Cut-off Current	I_{CEX}	$V_{CE} = -30\text{V}$, $V_{EB(OFF)} = -3\text{V}$	-	-	-50	nA
Base Cut-off Current	I_{BL}	$V_{CE} = -30\text{V}$, $V_{EB(OFF)} = -3\text{V}$	-	-	-50	nA
DC Current Gain	h_{FE}	$V_{CE} = -1\text{V}$, $I_C = -0.1\text{mA}$	60	-	-	-
		$V_{CE} = -1\text{V}$, $I_C = -1\text{mA}$	80	-	-	-
		$V_{CE} = -1\text{V}$, $I_C = -10\text{mA}$	100	-	300	-
		$V_{CE} = -1\text{V}$, $I_C = -50\text{mA}$	60	-	-	-
		$V_{CE} = -1\text{V}$, $I_C = -100\text{mA}$	30	-	-	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -10\text{mA}$, $I_B = -1\text{mA}$	-	-	-0.25	V
		$I_C = -50\text{mA}$, $I_B = -5\text{mA}$	-	-	-0.40	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = -10\text{mA}$, $I_B = -1\text{mA}$	-0.65	-	-0.85	V
		$I_C = -50\text{mA}$, $I_B = -5\text{mA}$	-	-	-0.95	V
Transition Frequency	f_T	$V_{CE} = -20\text{V}$, $I_C = -10\text{mA}$ $f = 100\text{MHz}$	250	-	-	MHz
Output Capacitance	C_{OBO}	$V_{CB} = -5\text{V}$, $f = 1\text{MHz}$, $I_E = 0$	-	-	4.5	pF
Input Capacitance	C_{OBI}	$I_C = 0$, $V_{EB} = -0.5\text{V}$; $f = 1\text{MHz}$	-	-	10	pF
Noise Figure	N_F	$I_C = -0.1\text{mA}$, $V_{CE} = -5\text{V}$ $R_S = 1\text{k}\Omega$, $f = 1\text{kHz}$	-	-	4	dB
Delay Time	t_D	$V_{CC} = -3\text{V}$, $V_{BE(off)} = -0.5\text{V}$	-	-	35	ns
Rise Time	t_R	$I_C = -10\text{mA}$, $I_{B1} = I_{B2} = -1\text{mA}$	-	-	35	ns
Storage Time	t_S	$V_{CC} = -3\text{V}$, $I_C = -10\text{mA}$	-	-	225	ns
Fall Time	t_F	$I_{B1} = I_{B2} = -1\text{mA}$	-	-	75	ns

Ratings and Characteristic Curves-NPN (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C









Fig 4 $V_{BE(on)}$ vs. I_C


Ratings and Characteristic Curves-PNP (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)



Package Outline Dimensions (Unit: mm)



Package Outline Dimensions (Unit: mm)



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.