


Features

- Epitaxial planar die construction
- Mounting cost and area can be cut in half
- Built-in biasing resistors, $R_1 \neq R_2$

HF

Mechanical Data

- Case : SOT-353
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



SOT-353

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
UMG8N	SOT-353	3000 pcs / Tape & Reel	G8

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Supply Voltage	V_{CC}	50	V
Input Voltage	V_{IN}	-5 to +30	V
Output Current	I_O	100	mA
Output Current	$I_{C(\text{Max.})}$	100	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	150	mW
Operating Junction Temperature Range	T_J	-55 ~ +150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Input Voltage	$V_{I(off)}$	$V_{CC} = 5V, I_o = 100\mu A$	0.5	-	-	V
	$V_{I(on)}$	$V_O = 0.3V, I_o = 5mA$	-	-	1.3	V
Output Voltage	$V_{O(on)}$	$I_o = 5mA, I_i = 0.25mA$	-	-	0.3	V
Input Current	I_i	$V_i = 5V$	-	-	1.8	mA
Output Current	$I_{O(off)}$	$V_{CC} = 50V, V_i = 0V$	-	-	0.5	μA
DC Current Gain	G_i	$V_O = 5V, I_o = 10mA$	80	-	-	-
Input Resistor	R_1		3.29	4.7	6.11	k Ω
Resistance ratio	R_2/R_1		8	10	12	
Gain-Bandwidth Product	f_T	$V_{CE} = 10V, I_E = 5mA, f = 100MHz$	-	250	-	MHz

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Input Voltage vs Output Current




Fig 2 Output Current vs Input Voltage




Fig 3 DC Current Gain vs Output Current





Fig 4 Output Voltage vs Output Current


Package Outline Dimensions (Unit: mm)



SOT-353		
Dimension	Min.	Max.
A	2.00	2.20
B	1.15	1.35
C	0.85	1.05
D	0.15	0.35
E	0.25	0.40
F	1.20	1.40
G	0.60	0.70
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40

Mounting Pad Layout (Unit: mm)

SOT-353



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.